

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

June 3, 1955
(Date)Hobbs, New Mexico
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corporation
(Company or Operator)Eddy State "AG" -
(Lease)McDaniel and Beschert
(Contractor)

Well No. 2 in the NE 1/4 NW 1/4 of Sec. 36 T. 26-S, R. 31-E, NMPM, North Mason Delaware Pool, Eddy County.

The Dates of this work were as follows: May 29-31, 1955

Notice of intention to do the work ~~was~~ (was not) submitted on Form C-102 on _____, 19____, and approval of the proposed plan ~~was~~ (was not) obtained.
(Cross out incorrect words)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Ran 22 Jts (906') 8-5/8" OD 28# Gr H-40 SS casing. Set and cemented at 918' in two stages. First stage with 300 sacks regular Neat cement. Maximum pressure 350#. Circulated approximately 15 sacks cement thru DV tool at 367'. Second stage with 225 sacks Neat thru DV tool. Maximum pressure 200#. Circulated approximately 75 sacks cement. Job complete by Howco 10:15AM 5-30-55.

After waiting over 24 hours, tested 8-5/8" casing with 1000# for 30 minutes. There was no drop in pressure. Drilled out DV tool. Tested with 1200# for 30 minutes. No drop in pressure. Drilled cement plug and tested below casing shoe with 800# for 30 minutes. No drop in pressure.

Witnessed by: Glenn Stach (Name) Gulf Oil Corporation (Company) Drilling Foreman (Title)

Approved: OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: E. J. Jay
Position: Area Supt. of Prod.
Representing: Gulf Oil Corporation
Address: Box 2167, Hobbs, N. M.

(Title)

(Date)