

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRI
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424. ✓

5. LEASE DESIGNATION AND SERIAL NO.

LC 031705-E

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Poker Lake

8. FARM OR LEASE NAME
Jennings Inc. - Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA
Section 20,
T-24-S, R-31-E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

PAULEY PETROLEUM INC. ✓

3. ADDRESS OF OPERATOR

930 Petroleum Life Bldg., Midland, Texas

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

660' from North Line and 660' from East Line,
Section 20, T-24-S, R-31-E.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3519.22 GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well spudded at 11:30 am, April 27, 1965.

Propose to drill 3-3/4" hole, with rotary, from surface to approx. 1000'-1020'.
Seven-inch (7") O.D. surface casing will be run to approx. 980'-1000', and cemented
with 200 sacks cement to surface.
A 6-1/4" hole will then be drilled, with rotary, to coring point (at approx. 4395')
and well cored to total depth.

RECEIVED

MAY 21 1965

O. C. C.
ARTESIA, OFFICERECEIVED
MAY 19 1965
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO(NOTE: Verbal permission, regarding above change of plans, granted by U.S.G.S. Office,
Artesia, New Mexico, on April 26, 1965.)

18. I hereby certify that the foregoing is true and correct

SIGNED J. C. HammerTITLE AgentDATE May 10, 1965

(This space for Federal or State office use)

APPROVED BY
CONDITION OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.