

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN THE
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 041705-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Dry Hole		7. UNIT AGREEMENT NAME Pedra Lake	
2. NAME OF OPERATOR PAULEY PETROLEUM INC.		8. FARM OR LEASE NAME Howard W. Jennings Inc. - Pedra!	
3. ADDRESS OF OPERATOR 930 Petroleum Life Bldg., Midland, Texas		9. WELL NO. 1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' from North Line and 660' from East Line, Section 20, T-24-S, R-31-E.		10. FIELD AND POOL, OR WILDCAT Wildcat (Delaware)	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3519.22 GR	
11. SEC., T., R., M., OR B.L. AND SURVEY OR AREA Section 20, T-24-S, R-31-E		12. COUNTY OR PARISH El Paso	
13. STATE New Mexico			

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well plugged and abandoned in accordance with U.S.G.S. specifications on May 3, 1965.

3/3/65:

T. D. 4302'. Cement plugs (Class A cement) placed as follows:

24' plug at surface from 0'-24'

30 sack plug from 915'-1059'

30 sack plug from 2622'-2776'

30 sack plug from 4301'-4455'

Displaced all cement with mud.

Installed required well marker.

NOTE: Approximate date for final well site inspection is June 1, 1965.

(NOTE: Discussed the plugging and abandonment procedures and received verbal permission to plug and abandon well from U.S.G.S. Office, Artesia, New Mexico, on May 3, 1965.)

18. I hereby certify that the foregoing is true and correct

SIGNED J. C. HammerTITLE AgentDATE May 10, 1965

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.