

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other Instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-031963

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

NONE

7. UNIT AGREEMENT NAME

NONE

8. FARM OR LEASE NAME

M. M. Stewart Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated Del.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 4, T-24-S, R-31-E

12. COUNTY OR PARISH

Eddy

13. STATE

N. M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

TEXACO Inc.

3. ADDRESS OF OPERATOR

P. O. Box 728 - Hobbs, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surfaceWell located 660' from the North Line, and 660' from the East
Line of Section 4, T-24-S, R-31-E, Eddy County, N. M.

14. PERMIT NO.

Regular

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

3435' (D. F.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETION ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The subject well has been plugged and abandoned as follows:

1. With 7 5/8" O. D. Casing Cemented at 566', none was recovered.
The following plugs were set:
2. 25 Sx. Cement Plug 4275' to 4400'.
3. 25 Sx. Cement Plug 3525' to 3700'.
4. 50 Sx. Cement Plug 2650' to 2900'.
5. 25 Sx. Cement Plug 525' to 650'. (CIBP at 525')
6. 25 Sx. Cement Plug 400' to 525'.
7. The surface plug was 25 Sx. 0' to 125', a 4" marker extending 4' above ground level was installed, location cleaned for inspection by the USGS representative. Plug and abandon complete December 3, 1966.

18. I hereby certify that the foregoing is true and correct

SIGNED

Dan Gillett
(This space for Federal or State office use)

TITLE Assistant District

Superintendent

DATE December 12, 1966

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

FEB 20 1967
R. L. BECKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

RECEIVED
DEC 13 1966
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO