

NO. OF COPIES RECEIVED	6
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	1
LAND OFFICE	1
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-101
Revised 1-1-65

5A. Indicate Type of Lease	
STATE <input checked="" type="checkbox"/>	FEE <input type="checkbox"/>
5. State Oil & Gas Lease No.	
K-6783	

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. Type of Work		7. Unit Agreement Name	
b. Type of Well OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		None	
2. Name of Operator		8. Farm or Lease Name	
J.P. LEYENDECKER, JR		Hennifin State	
3. Address of Operator		9. Well No. B.D. Hennifin State No. 1	
P.O. Box 38, Roswell, New Mexico 88201		10. Field and Pool, or Wildcat	
4. Location of Well UNIT LETTER <u>C</u> LOCATED <u>330'</u> FEET FROM THE <u>North</u> LINE AND <u>330'</u> FEET FROM THE <u>West</u> LINE OF SEC. <u>16</u> TWP. <u>26S</u> RGE. <u>24E</u> NMPM		Wildcat	
12. County			
Sddy			
19. Proposed Depth		19A. Formation	
600'		Delaware	
20. Rotary or C.T.		Both	
21. Elevations (Show whether DF, RT, etc.)		21A. Kind & Status Plug. Bond	
3788' GL		\$ 5000.00	
21B. Drilling Contractor		22. Approx. Date Work will start	
Wm. Brady		Nov. 8, 1967	

23.

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
7-7/8"	5 1/2"	14 lb.	490'	125	490'
					5225 FT

Contractor's rotary tools to Casing point.
Operator's own cable tools thereafter

APPROVAL VALID
FOR 90 DAYS UNLESS
DRILLING COMMENCED

EXPIRES

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed J.P. Leyendecker, Jr. Title Operator Date November 3, 1967

(This space for State Use)

APPROVED BY W.D. Grassett TITLE DATE 11/3/67

CONDITIONS OF APPROVAL, IF ANY:

Cement must be circulated to
surface behind 5 1/2" casing

5 1/2"