

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TWO COPIES
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL GAS WELL OTHER Dry Hole

2. NAME OF OPERATOR
Sinclair Oil Corporation

3. ADDRESS OF OPERATOR
P. O. Box 1920, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface
1980' FWL and 660' FNL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5. LEASE DESIGNATION AND SERIAL NO.
NM 050200-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Guadalupe Ridge Unit

9. WELL NO.
1

10. FIELD AND POOL, OR WILDCAT
Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
22-T26S-R21E

12. COUNTY OR PARISH
Eddy

13. STATE
New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF <input type="checkbox"/>	PULL OR ALTER CASING <input type="checkbox"/>	WATER SHUT-OFF <input type="checkbox"/>	REPAIRING WELL <input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	MULTIPLE COMPLETE <input type="checkbox"/>	FRACTURE TREATMENT <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	ABANDON* <input checked="" type="checkbox"/>	SHOOTING OR ACIDIZING <input type="checkbox"/>	ABANDONMENT* <input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	(Other) <input type="checkbox"/>	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

PROPOSE TO PLUG AND ABANDON AS FOLLOWS:

TD 8000'. With hole filled with heavy mud laden material, spot 20 sacks cement plug approx. 7250-7350'.
Spot 20 sacks cement plug approx. 6000-6100'.
Set C.I. plug in 7"OD casing @ 5180' and dump approx. 3 sks. cement 5145-80'.
Cut 7"OD casing @ approx. 3950' and pull.
Spot 60 sacks cement plug in top of 7"OD csg stub approx. 3800'-4000'.
Spot 60 sacks cement plug approx. 2770-2970' (Glorietta).
Spot 30 sacks cement plug approx. 2050-2150' bottom of 8-5/8"OD casing.
Load hole w/fresh water and leave standing full.

RECEIVED
JAN 15 1969
O. C. C.
ARTESIA, OFFICE

Confirming verbal approval to P&A by phone conversation 1-13-69 between Mr. M. D. Payne, Engineer Sinclair Oil Corporation, Hobbs, New Mexico and Mr. J. A. Knaut, Dist. Engr., USGS, Artesia, New Mex.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Superintendent DATE 1-15-69

(This space for Federal or State office use)

APPROVED BY [Signature] TITLE DISTRICT ENGINEER DATE JAN 17 1969

CONDITIONS OF APPROVAL, IF ANY:

Orig & cc: USGS, Artesia, N.M.
cc: Mrs. M. M. Rhea, Santa Fe, N.M. See instructions on Reverse Side
cc: Partners
cc: Southern Region (West Texas)