

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRI  
(Other instructive  
verse side)DATE  
on re-Form approved.  
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

NM 050200-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Guadalupe Ridge Unit

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

22-T26S-R21E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> Plug and Abandon	RECEIVED
2. NAME OF OPERATOR SINCLAIR OIL CORPORATION	Atlantic Richfield Co.
3. ADDRESS OF OPERATOR P. O. Box 1920, Hobbs, New Mexico 88240	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See space 17 below.) At surface 1980' FWL and 660' FNL.	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 7267' GR

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

X

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

## PLUGGED AND ABANDONED AS FOLLOWS:

Filled hole with heavy mud laden material, spotted 20 sacks cement plug 7250-7350'.

Spot 20 sacks Class H cement plug 6000-6100'.

Set C.I. plug in 7"OD casing @ 5180', dumped 3 sacks cement 5145-80'.

Cut 7"OD casing @ 3950' and pulled.

Spot 60 sacks Class H Cement plus 1% CFR<sub>2</sub> 3800-4000' top of 7"OD casing stub.Spot 60 sacks Class H Cement plus 1% CFR<sub>2</sub> across Glorietta 2700-2970'.Spot 30 sacks cement Class H plus 1% CFR<sub>2</sub> 2050-2150' bottom of 8-5/8"OD casing.

Loaded hole from 2050' to surface with fresh water.

Cut off 8-5/8"OD casing head, welded on 8-5/8"OD casing nipple on casing to ground level, tacked 1/4" steel plate on top of casing w/bleeder valve.

Well is in National Forest  
and is to be converted to  
a water-supply well by  
the Forest Service

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Superintendent

DATE

1-20-69

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

OCT 3 1974

CONDITIONS OF APPROVAL, IF ANY:

Orig<sup>4</sup>cc: UZOS, Artesia, N.M.

cc: Mrs. M. M. Rhea, Santa Fe, N.M.

cc: Partners

cc: Southern Region (West Texas)

cc: file

\*See Instructions on Reverse Side