

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on
reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM - 0503

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

-

7. UNIT AGREEMENT NAME

-

8. FARM OR LEASE NAME

Cotton Draw Unit

9. WELL NO.

68

10. FIELD AND POOL, OR WILDCAT

Paduca Morrow Gas

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 12, T-25-S, R-31-E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

1. OIL ☐ GAS ☒ OTHER ☐
WELL ☐ WELL ☒
2. NAME OF OPERATOR
TEXACO Inc.
3. ADDRESS OF OPERATOR
P. O. Box 728 - Hobbs, New Mexico 88240
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface Well is located 2310' FNL & 1980' FNL of
Section 12, T-25-S, R-31-E, Unit Letter 'F', Eddy County,
New Mexico.

14. PERMIT NO.

Regular

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3457' (DF)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	<input type="checkbox"/>	PULL OR ALTER CASING	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	MULTIPLE COMPLETE	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	ABANDON*	<input checked="" type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	CHANGE PLANS	<input type="checkbox"/>

(Other) *Morrow - Recomplete in Wolf- X camp

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	<input type="checkbox"/>	REPAIRING WELL	<input type="checkbox"/>
FRACTURE TREATMENT	<input type="checkbox"/>	ALTERING CASING	<input type="checkbox"/>
SHOOTING OR ACIDIZING	<input type="checkbox"/>	ABANDONMENT*	<input type="checkbox"/>

(Other) _____
(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

1. Rig up. Kill well. Install BOP. Pull production equipment.
2. Set CIBP @ 14,100'. Dump 10 sx Class H Cement on plug. Abandon Morrow zone.
3. Perforate 5-1/2" OD csg w/1 JSPF in Wolfcamp @ 12,895', 12,939', 44', 63', 68' & 12,972'.
4. If necessary, acidize perforations 12,895'-12,972' w/3000 gals 20% super retarded acid containing 350 SCF Nitrogen/bbl.
5. Flush w/2% KCL water. Swab.
6. Install production equipment. Test and place on production.

RECEIVED RECEIVED

JUL 21 1976

JUL 19 1976

O. C. C.
ARTESIA, OFFICEU. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Asst. Dist. Supt.

DATE 7-15-76

(This space for Federal or State office use)

TITLE

DATE

APPROVED BY
CONDITIONS OF APPROVAL IF ANY:JUL 19 1976
L. L. BECKING
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side