

RECEIVED

MAY 17 1972

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPL
(Other instructions
verse side)FE
reForm approved.
Budget Bureau No. 42-R1424

Copy 2 of 3

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
ARTESIAL APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. NM 0472258
2. NAME OF OPERATOR CITIES SERVICE OIL COMPANY		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P.O. Box 69, Hobbs, New Mexico 88240		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980 ¹ FNL & 1980 ¹ FEL of Sec. 27-T25S-R24E, Eddy Co. N.Mex.		8. FARM OR LEASE NAME Government M
14. PERMIT NO.		9. WELL NO. 3
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3730 DF		10. FIELD AND POOL, OR WILDCAT Undes. Washington Ranch Morrow
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 27-T25S-R24E
		12. COUNTY OR PARISH Eddy
		13. STATE N.Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Setting & Cementing 5 1/2"

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

T.D. 6500 Lme. Prep to drill ahead. Drilled to a T.D. of 6500¹ and ran 147.3 jts (4774.86¹) 5 1/2" OD 14# K-55, 53 jts (1710.96¹) 5 1/2" OD 15.5# K-55 casing set and cemented @ 6500¹ W/150 sacks Class C W/8# salt + 3/4% CFR-2 Cement. Plug down @ 2:35 P.M. on 5-13-72. Ran temp. survey. Top of cement @ 5180¹. WOC 24 hrs. Tested 5 1/2" casing and rams to 1500 psi for 30 minutes with no drop in pressure.

MAY 16 1972
U. S. GEOLOGICAL SURVEY
ALBUQUERQUE, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Dist. Admin. Supervisor

DATE 5-15-72

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side