

MOCC COPY

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE
(Other instructions
reverse side)Form approved
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

LC-061716

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Superior - USA

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Washington Ranch Dela.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

11-26S-24E

12. COUNTY OR PARISH

13. STATE

Eddy

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL ☐ GAS ☒ OTHER
WELL ☐ WELL ☒

RECEIVED

2. NAME OF OPERATOR

J.M. Huber Corporation

DEC 21 1977

3. ADDRESS OF OPERATOR

1900 Wilco Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface1980' FNL & 2050' FEL, Section 11,
T-26-S, R-24-E

14. PERMIT NO.

Blanket

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3752' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

- 1) MIRU casing pullers,
- 2) POH w/3/4" rods and pump,
- 3) Spot 100' cement plug (20 sx) from 1600' to 1500' to cover perforations
1527', 1532', 1539', 1546', 1556' and 1564',
- 4) Spot 100' cement plug (20 sx) from 850' to 750',
- 5) Place 20 sx cement @ surface,
- 6) Release rig,
- 7) Place well Marker,
- 8) Clean up location,
- 9) Rip pad and road.

RECEIVED
DEC 19 1977
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert G. Setzler

TITLE Dist. Prod. Manager

DATE 12-16-77

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE ACTING DISTRICT ENGINEER

DATE DEC 20 1977