

NMOCC COPY UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN 30
(Other, instruct
reverse side)

ICATE*
on re-

Form approved
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-061716

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

1. ☐ OIL
WELL ☐ GAS
WELL ☒ OTHER

2. NAME OF OPERATOR

J. M. Huber Corporation

3. ADDRESS OF OPERATOR

1900 Wilco Building, Midland, Texas 79701

O. C. C.
ARTESIA, OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space (f below)
At surface

1930' FNL & 2050' FEL, Section 11, T-26S, R-24E

30-015-20660

7. UNIT AGREEMENT NAME

8. FIRM OR LEASE NAME

Superior USA

9. WELL NO

1

10. FIELD AND POOL, OR WELLSAT

Washington Ranch Delawa

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 11, T-26S, R-24E

12. PERMIT NO.

13. ELEVATION (Show whether OF, BT, OR etc.)

Blanket

3752' CR

Eddy

N. M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PUMP OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETION

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(Other)

(NOTE: Report results of multiple completion or Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 1) MI RU,
- 2) POH w/3/4" rods and pump,
- 3) Circulated 4-1/2" csg. w/gelled mud (Bentonite),
- 4) Spotted 100' cement plug (20sx) from 1600' to 1500' to cover perforations 1527, 1532', 1539', 1546', 1556' and 1564',
- 5) Spotted 100' cement plug (20sx) from 850' to 750',
- 6) Placed 20 sx cement @ surface,
- 7) Released rig,
- 8) Placed well Marker,
- 9) Cleanup location,
- 10) Rippad and road.

RECEIVED
APR 1978
BY [Signature]
FRESH MEAT

18. I hereby certify that the foregoing is true and correct.

SIGNED

Robert G. Setzler

TITLE Dist. Prod. Mgr.

DATE February 2, 1978

(This space for Federal or State office use)

APPROVED BY

[Signature]

TITLE

ACTING DISTRICT ENGINEER

DATE

APR 4 - 1978

CONDITIONS OF APPROVAL, IF ANY