

NO. OF COPIES RECEIVED

3

DISTRIBUTION		
SANTA FE	/	
FILE	/	
U.S.G.S.		
LAND OFFICE		
OPERATOR	/	

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

AUG 4 1972

O. C. C.
ARTESIA, OFFICEForm C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease

State ☐Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole	7. Unit Agreement Name
2. Name of Operator Black River Corporation /	8. Farm or Lease Name Thurman
3. Address of Operator 620 Commercial Bank Tower, Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER C, -330 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 21 TOWNSHIP -265 RANGE 24E NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3773.5 GL	12. County Eddy

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:PERFORM REMEDIAL WORK ☐PLUG AND ABANDON ☒TEMPORARILY ABANDON ☐PULL OR ALTER CASING ☐CHANGE PLANS ☐OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐COMMENCE DRILLING OPNS. ☐CASING TEST AND CEMENT JOB ☐OTHER ☐ALTERING CASING ☐PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

The subject well was drilled to a total depth of 8015 feet and proved to be non-productive. Verbal approval to plug and abandon was given by Mr. Bill Gressett on July 31, 1972. 8-5/8" 24 lb/ft. surface casing had been set at 745 feet and cemented w/350 sacks cement with cement circulated to surface. The following cement plugs were set to permanently plug and abandon.

Plug No.	Depth Top Plug	Depth Bottom Plug	180 sx Plug	Formation and Top
1	7660	7760	35	Morrow Clastic - 7682
2	6550	6650	35	Strawn 6605
3	3850	3950	35	Bone Spring 3902
4	2000	2100	35	Delaware 520
5	700	800	35	in & out of surface cas.
6	0	120	25	surface plug

Metal cap was welded on 8-5/8" surface and appropriate maker installed

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. T. Berry J. T. BerryTITLE AgentDATE 8/2/72APPROVED BY W. A. GressettTITLE Manager, Oil ConservationDATE Aug 2 1972

CONDITIONS OF APPROVAL, IF ANY: