	ર પંચ ક્લ્પના દિવસ	, C. J., CICPY	Corry 6 SF
Form 9-331 (May 1963)	UI ED STATES DEPARTMENT OF THE INTER GEOLOGICAL SURVEY	SUBMIT IN TRIE ATE (Other instruction, ') re IOR verse side)	1 Manual "
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals.)			6. IF INDIAN, ALIOTIEE OR TRISF NAME
1. WELL GAS WELL OTHER Dry Hole 2. NAME OF OPERATOR			8. FARM OR LEASE NAME
Black River Corporation			BR-Federal 4
3. ADDRESS OF OPERATOR			9. WELL NO.
4. 100 ATION OF WELL (Re See a so space 17 below	FNL & 2087' FWL Section 4	7 State requirements,*	2 10. FIELD AND POOL, OR WILDCAT Washington Ranch Morrow 11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA Sec. 4, T26S, R24E
14. PERMIT NO.	15, BLEVAT(DNS (Show whether D	F, RT, GR, etc.)	12. COUNTY OR PARISH 13. SPATE
	3797 GL		Eddy New Mexico
16.	Check Appropriate Box To Indicate 1	Nature of Notice, Report, or (	Other Data
NOTICE OF INTENTION TO: SUBSEC		UENT REPORT OF:	
TEST WATER SHUT-OF		WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE		SHOOTING OF ACIDIZING	ABANDONMENT
REPAIR WELL (Other)	CHANGE PLANS		s of multiple completion on Well pletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all portinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

It is intended to plug and abandon on 11/2/72 in the following manner as per verbal plugging instructions received from Mr. Knauf on 11/2/72. At a total depth of 7350 feet, at which time no commercially productive zones had been encountered a 30 sx. cement plug will be spotted from 7100' to 7000'; a 30 sx. cement plug will be spotted from 6040' to 5940'; 30 sx. cement plug from 3720' to 3620'; 30 sx. cement plug from 2300' to 2200'; 30 sack cement plug from 625' to 525' which is 50 feet below and above the 8-5/8" casing. A 20 sx. cerent will be set at the surface. The 8-5/8" casing will be capped with a steel plate and an appropriate marker welded to the steel plate. The USGS will be notified when location is ready for final inspection.

RECEIVED . ANS1373 STENAL DAY MEXICO y that the foregoing is true and correct 18. I hereby certif 1/29/73 J. T. BerryTITLE Agent DATE SIGNED (This space ffice use) TITLE DATE ... NY IF BEEKNIAN ACTING DISTRICT ENGINEER \*See Instructions on Reverse Side