		N.M.O.	C. C. COLY		Capy 4 SI-	
Form 9-331 (May 1963)	UN! .D ST DEPARTMENT OF T GEOLOGICAL	ATES HE INTERIOI	SUBMIT IN TRIPLI		eau No. 42-R1424. N AND SERIAL NO. 9	
Do not use the	NDRY NOTICES AND is form for proposals to defil or to Use "APPLICATION FOR PERM	REPORTS ON deepen or plug back 11T—" for such prope	N WELLS to a different reservoir. Dsals.)			
				7. UNIT AGREEMENT NAME		
OIL WELL GAS WELL OTHER Dry Hole 2. NAME OF OPERATOR				8. FARM OR LEASE NAME		
Black River Corporation /				BR Federal 4		
 620 Commercial Bank Tower, Midland, Texas 79701 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1985' FNL & 2087' FWL of Section 4 				2 10. FIELD AND POOL, OR WILDCAT Washington Ranch Morrow 11. SEC. T. R. M. OB BLE. AND SUBVEY OR ABEA Sec. 4, T26S, R24E		
14 DEP VIT NO. 15. ELEVATIONS (Show whether DF, BT, CB, etc.)				12. COUNTY OR PARISH 3. STATE		
14. PERMIT NO. 30-015-7		797 G.L.		Eddy	New Mexico	
18.	Check Appropriate Box	To Indicate Nat	ure of Notice, Report, or	Other Data		
	QUENT REPORT OF:					
TEST WATER BHUT FRACTURE TREAT SHOOT OR ACIDIZE	C-OFF PULL OR ALTER C MULTIPLE CON PUL ABANDON®		WATER SHUT-OFP FRACTURE TREATMENT SHOUTING OR ACIDIZING	REPAIRING ALTERING ABANDON	CASING	
(Other)	CHANGE PLANS	·	(Cther) (NOTE: Report results of multiple completion on Wel' Completion or Recompletion Report and Log form.)			

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The subject well was plugged and abandoned on November 2, 1972 in accordance with verbal plugging instructions and permission received from Mr. Knauf on 11/2/72 in the following manner: At a total depth of 7350 feet, at which time no commercially productive zones had been encountered a 30 sack cement plug was spotted from 7100' to 7000'; a 30 sack cement plug was spotted from 3720' to 3620'; 30 sack cement plug from 3720' to 3620'; 30 sack cement plug from 625' to 525' which was 50 feet below and above the ε -5/8" casing. A 20 sack cement was set at the surface. The 8-5/8" casing was capped with a steel plate and an appropriate marker welded to the steel plate. The USGS will be notified when location is ready for final inspection.

Rn

			NOV U. S. GEOLO ARTESIA, N	CEIVED 161972 GICAL SHILLY W MEXICO
19. I hereby certify that the foregoing is true ind correct SIGNED J. T. Berry	ry _{ITLE}	Agent	DATE	11/15/72
(This spice for Federal of State office use)	TITLE		DATE	
KOV 2-15	e Instructions	on Reverse Side		