

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM-0426938-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐ **Dry Hole** **MAR 28 1973**

2. NAME OF OPERATOR

David Fasken

O. C. C.

3. ADDRESS OF OPERATOR

ARTESIA, OFFICE

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Inexco "10" Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 10, T-25-S, R-25-E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

14. PERMIT NO.

30-015-20781

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3512' G.L. - 3528' K.B.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☒

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

T.D. 11,950', 9-5/8" casing at 5380', top cement 2610', 13-3/8" at 340' cement to surface.

Proposed Plugging Procedure

30 sx. cement plug 10,950' - 11,050'

30 sx. cement plug 10,100' - 10,200'

60 sx. cement plug 9,200' - 9,400'

60 sx. cement plug 7,400' - 7,600'

60 sx. cement plug 5,250' - 5,450'

Set C.I. bridge plug @ 2800'

Out 9-5/8" casing at 2500' ± and pull

60 sx. cement plug 2400' - 2600'

70 sx. cement plug 290' - 390'

15 sx. cement plug top of 13-3/8" casing

Tentative Tops

Narrow Line 10,974'

Top Strawn 10,124'

Top Wlop. Line 9,350'

Top Wlop. Zone 7,580'

Int. Casing Shoe 5,380'

Casing Stub 2,500'

Surface Casing 340'

Approved per telephone conversation 3-15-73 Henry to Knauf.

18. I hereby certify that the foregoing is true and correct

James B. Henry

SIGNED

TITLE

Agent

DATE

3-22-73

(This space for Federal or State office use)

APPROVED BY
SIGNATURE OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
MAR 28 1973
H. L. BECKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.