	N.M.O.C.	C. COM		
Form 9-331 (May 1963)	UN D STATES DEPARTMENT OF THE INTER	SUBMIT IN TRIPL 'E' (Other instructions 're VOR verse side)	H = Hudget Rureeu No 49_R1394	
	GEOLOGICAL SURVEY		NM-0526348-A	
	NDRY NOTICES AND REPORTS is form for proposals to drill or to deepen or plug Use "APPLICATION FOR PERMIT—" for such		6. IF INDIAN, ALLOTTEE OF TRINE NAME	
1. OIL C GAS WELL WELL	, other Dry Hole	SECEIVED	7. UNIT AGREEMENT NAME	
	Exploration, Inc.	1 R a = 1974	8. FARM OR LEASE NAME Marathon-Federal	
3. ADDEESS OF OPERAT	OR		9. WELL NO.	
		⊖ C. C. y State feqi£intent® ≤ CE	10. FIELD AND POOL, OR WILDCAT Wildcat 11. SEC., T., R., M., OR BLK. AND SCRVEY OR ABEA	
30-0 S-7	Sec. 22, T26S, R25E			
Issued June	15. ELEVATIONS (Show whether r 6. 1973 3635 GR 3651		Eddy New Mexico	
18.	Check Appropriate Box To Indicate			
NOTICE OF INTENTION TO :		SUBSEQ	SUBSEQUENT REPORT OF:	
TEST WATER SHUT	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL	
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING	
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMEN1* X_	
REPAIR WELL	CHANGE PLANS	(Other) (Note: Report result Completion or Recom	s of multiple completion on Well	

17. DESCRIPT PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markets and zones pertinent to this work.) *

The subject well was drilled to a total depth of 11,120 feet and commercial production was not encountered. Well was plugged 7/30/73 in the following manner: 100 ft cement plug from 10,600 up to 10,500' across the Devonian; 100 ft. cement plug from 9450 up to 9350' across top of Morrow; 100 ft cement plug from 8600 up to 8500 ft. across top of Strawn; 100 ft. cement plug from 7500 up to 7400' across top of Wolfcamp; a 100 ft. cement spacer plug from 6100' - 6000'; 100 ft. cement plug from 4875 to 4775' in and out of the 9/5/8'' intermediate casing set at 4828'. No casing was pulled and the intervals between cement plugs was filled with mud of 25% minimum gel strength. A 20 ft. plug was placed at the surface and an appropriate dry hole marker was installed at the surface. The Survey will be notified when the location is ready for an abandonment inspection. Verbal permission to plug granted 7/28/73.

		N.S. COL. 27	Nep 2000 14
18. I hereby certify that the foregoing is true and cor	rect		
SIGNED		Agent	DATE7/31/73
(This space for Federal or State office use)			DATE
APR 3-151A APR 3-151A BEEKWAN ACTIVE DISTRICT ENCONEER	*0,00 °.946	ingging for the	