

NEW MEXICO OIL CONSERVATION COMMISSION

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- RECEIVED		7. Unit Agreement Name
2. Name of Operator The Superior Oil Company		8. Farm or Lease Name Parks Com
3. Address of Operator P. O. Box 1900, Midland, Texas 79701		9. Well No. 1
4. Location of Well UNIT LETTER <u>F</u> <u>1650</u> FEET FROM THE <u>North</u> LINE AND <u>1650</u> FEET FROM THE <u>West</u> LINE, SECTION <u>5</u> TOWNSHIP <u>25-S</u> RANGE <u>26-E</u> N.M.P.M.		10. Field and Pool, or Wildcat Undesignated - Penn
15. Elevation (Show whether DF, RT, GR, etc.) KB: 3375' GL: 3357'		12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 12-1/4" hole to 1700' on August 3, 1973, and ran 9-5/8", 36#, J-55, ST&C casing to 1700'. Cemented with 300 sacks class "C" cement with full returns throughout. Top cement by survey at 850'. Installed and tested BOP, Hydril, and casing to 2000 psi for 30 minutes. Drilled out with 8-1/2" bit at 7:00 PM on August 4, 1973, after WOC for 26 hours, 25 minutes.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Terry Clay Terry Clay TITLE Petroleum Engineer DATE August 15, 1973

APPROVED BY W. A. Bennett TITLE Oil and Gas Inspector DATE AUG 16 1973

CONDITIONS OF APPROVAL, IF ANY: