

PERRY R. BASS
 POKER LAKE UNIT #41
 PROPOSED DRILLING AND COMPLETION PROCEDURE

Page 9

Casing and Tubing Data:

OD	#/Ft	Grd	Jt Strn. M #	Type Joint	Cplg or Jt OD	Min Collapse	Burst at MY	ID	Drift Dia
20"	94	H-40	487	ST&C	21.000	520	1530	19.124	18.936
13 3/8"	48	H-40	322	ST&C	14.375	770	1730	12.715	12.559
	54.5	K-55	547	ST&C	14.375	1130	2730	12.615	12.459
	61	K-55	633	ST&C	14.375	1540	3090	12.515	12.359
	68	K-55	718	ST&C	14.375	1950	3450	12.415	12.259
9 5/8"	40	N-80	916	Buttress	10.625	3090	5750	8.835	8.679
	40	N-80	737	LT&C	10.625	3090	5750	8.835	8.679
	43.5	N-80	825	LT&C	10.625	3810	6330	8.755	8.599
	43.5	S-95	960	LT&C	10.625	5600	7510	8.755	8.599
7 5/8"	39	S-95	800	ABC FL-4S	7.625	10600	10900	6.625	6.500
5"	18	N-80	422	X-line	5.360	10490	10140	4.276	4.151
2 7/8"	6.5	N-80	145	ABC Mod	3.668	9420	10570	2.441	2.347

RECEIVED

AUG-9 1973

U. S. GEOLOGICAL SURVEY
 ARTESIA, NEW MEXICO