

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.  
5. LEASE DESIGNATION AND SERIAL NO.

LC 068431

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT--" for such proposals.)1. OIL ☐ GAS ☐ OTHER ☒ Active Drilling Well **RECEIVED**

2. NAME OF OPERATOR

Perry R. Bass ✓

NOV - 7 1973

3. ADDRESS OF OPERATOR

Box 1178, Monahans, Texas 79756

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)

At surface

D.C.C.

ARTESIA, OFFICE

1980' FNL &amp; 1980' FEL of Section 21, Unit letter G.

7. UNIT AGREEMENT NAME

D. Poker Lake

8. FARM OR LEASE NAME

Poker Lake Unit

9. WELL NO.

41

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 21, T24S, R30E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3350' Est. Gr.

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) Spud date & 20" csg setting ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)\*

Spudded well at 9:30 PM, MDT, September 30, 1973.

Total Depth of 26" hole: 563'.

20" OD casing set as follows:

| No.<br>Jts. | Description                                               | Threads<br>Length | From   | To     |
|-------------|-----------------------------------------------------------|-------------------|--------|--------|
| ---         | Rotary correction                                         | 31.25             | 0.00   | 31.25  |
| 12          | 20" OD, 94#/ft. H-40, ST&C casing:                        | 444.34            | 31.25  | 475.59 |
| ---         | Halliburton baffle collar with plug<br>and sealing sleeve | 1.63              | 475.59 | 477.22 |
| 1           | 20" OD, 94#/ft., H-40, ST&C casing                        | 37.02             | 477.22 | 514.24 |
| ---         | Halliburton shoe*                                         | 2.10              | 514.24 | 516.34 |

\*Equipped with lateral exit ports.

Bottom 3 joints sand-blasted, welded and sealed with HOWCO weld; one  
positive-type centralizer on each of the bottom 3 joints. Cont'd on back.

18. I hereby certify that the foregoing is true and correct

SIGNED

*H. J. Murty, Jr.*

TITLE

Div. Prod. Clerk

DATE

November 2, 1973

(This space for Federal or State office use)

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

**APPROVED**  
NOV 6 - 1973  
*R. L. BEEKMAN*  
ACTING DISTRICT ENGINEER

\*See Instructions on Reverse Side

## Instructions

**General:** This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

**Item 4:** If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

**Item 17:** Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

867-851

Worked 20" casing to 516'; unable to go lower. Ran drill pipe with seal assembly set in baffle collar and cemented casing with 980 sacks Hauburton "light" (12.5 PPG slurry weight) containing 1/2# Flocele per sack, followed by 200 sacks class C containing 2% CaCl<sub>2</sub> (14.8 PPG slurry weight). Circulated out 100 sacks "light" cement. Plug down at 2:05 p.m., MDT, 10-2-73. Pump pressure 300 psi; seated plug and pressured to 1500 psi. 13 joints of 20" OD 94#/ft. H-40 ST&C casing set at 516'. Cut off conductor pipe; installed well head and levelling plate. Filled cellar to levelling plate with 16 yards of "Redi-mix" cement. Tested head to 600 psi. Commenced nipping up.

Started drilling new hole at 5:30 p.m., MDT, October 4, 1973.