

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FOR APPROVED
OMB NO. 1004-0137
Expires: December 31, 1991

5. LEASE DESIGNATION AND SERIAL NO.

LC-068431

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

POKER LAKE UNIT

8. FARM OR LEASE NAME, WELL NO.

POKER LAKE UNIT #41

9. API WELL NO.

30-015-20933

10. FIELD AND POOL, OR WILDCAT

WILDCAT DELAWARE

11. SEC. T. R. M., OR BLOCK AND SURVEY OR AREA

SEC 21, T24S, R30E

12. COUNTY OR PARISH
EDDOY

13. STATE
NEW MEXICO

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☒ GAS WELL ☐ DRY ☐ JAN 5 10 10 AM '93

b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RENVR. ☒ Other ☐

2. NAME OF OPERATOR

BASS ENTERPRISES PRODUCTION CO.

3. ADDRESS AND TELEPHONE NO.

P. O. BOX 2760 MIDLAND, TEXAS 79702-2760

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)

At surface 1980' FNL & 1980' FEL UNIT LETTER G. APTES

At top prod. interval reported below

At total depth SAME

14. PERMIT NO. DATE ISSUED

15. DATE SPUDDED 10-1-73 16. DATE T.D. REACHED 2-11-74 17. DATE COMPL. (Ready to prod.) NEW COMP. 12-9-92 18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 3359.6' GL, 3391' RKB 19. ELEV. CASINGHEAD -----

20. TOTAL DEPTH, MD & TVD 15,100 21. PLUG, BACK T.D., MD & TVD 7880' 22. IF MULTIPLE COMPL., HOW MANY* SINGLE 23. INTERVALS DRILLED BY X 24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* 7583' - 7593' (41 SHOTS) DELAWARE 25. WAS DIRECTIONAL SURVEY MADE NO

26. TYPE ELECTRIC AND OTHER LOGS RUN NONE THIS COMPLETION 27. WAS WELL CORRED NO

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
20"	94#	516'	26"	CIRCULATE TO SURF-1180'SX	NONE
13-3/8"	68,54,48#	3868'	17-1/2"	CIRCULATE TO SURF-4125 SX	NONE
9-5/8"	43.5, & 40#	11342'	12-1/4"	CIRCULATE TO SURF-1740 SX	NONE

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
7-5/8"	11073	14270'	450	-----	2-7/8"	7487'	7487' (SN)
5"	14061	14740'	145	-----			

31. PERFORATION RECORD (Interval, size and number)

4-JSPF 1-11/16" PIVOT GUN TOTAL
41 SHOTS 7583' - 7593'

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
7915'	SET CIBP W/ 35' CL "H" CEMENT
7583 - 7593'	6000 GALS VIKING 1-30 W/ ADDITIVE & 26000= 20/40 OTTAWA SAND

33.* PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
12-9-92		PUMPING 2-1/2" x 1-1/2" x 24' RHBC				PRODUCING	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BSL.	GAS—MCF.	WATER—BSL.	GAS-OIL RATIO
1-3-93	24	-----	→	16	16	52	1000
FLOW, TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BSL.	GAS—MCF.		WATER—BSL.	OIL GRAVITY-API (CORR.)
25	25	→	16	16		52	est. 39.0

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

USED ON LEASE 16 MCFPD

35. LIST OF ATTACHMENTS

NONE THIS COMPLETION

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED *R.C. Sanchez*

TITLE SENIOR PRODUCTION ENGINEER

DATE 1-4-93

*(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.
WOLFCAMP	12382'	12482'	SEE ATTACHED DST #1
MORROW	14095'	14238'	SEE ATTACHED DST #2
MORROW	14270'	14529'	SEE ATTACHED DST #3 MISRUN
MORROW	14555'	14706'	SEE ATTACHED DST #4
			SEE ATTACHED DST #5
			DST's NOT ATTACHED
			DST's were submitted with TA completion in 1974.

38. GEOLOGIC MARKERS

NAME	TOP	
	MEAS. DEPTH	TRUE VERT. DEPTH
T/DELAWARE LIME	3840'	3840'
T/DELAWARE SAND	3878'	3878'
T/BONE SPRING	7685'	7685'
T/WOLFCAMP	10560'	10560'