

LOCATION UNIT K, SEC 14, T-25S, R-24E SIGNED S.L. MUNSELL
EDDY COUNTY, N.M.

ZERO GL+17'

345'-(9 JTS) 20" 94 1/2 FT,
8" AND BUTTR. CS 6.
26" HOLE, CMT W/ GSOX
CMT CIRC.

3240' - (75 JTS) 13 3/8"
61 U/FT 8 RD ST & C
17 1/2" HOLE, CMT W/ 1700 SX
CMT CIRC. 1

9 1/8" CMT RETAINER @ ± 3325'

9 1/2" CMT RETAINER @ ± 5260'

10885' - 7" LINER TOP
CRIT W/ 400 SX

11.100' - 9 5/8" S-95 43.50 10/FT
B RD LTIC CNT W/ 300 SX
CNT TOP @ 4655
12 1/4" HOLE

14.414' - (78 JTS) 7" 31.81 4/FT
HYDRIL SUPER FJ P-110 + (7 JTS)
26 1/4" FT S-95 8ND LT & C.
8 1/2" HOLE
CMT W/ BOOM

16,505' - TD - 570' OH

4 SHOT / IPT SIZED W/ 75 SX (MT (3260'))

4 SHOT/1 FT SQZED W / 75 SX CMT (3340')

BELL CANYON PERITS 3289-3300 (1 JSPF) (SCH DLL
3-17-74)

— 9 1/2 CIBP # 5150' CAPPED W/ 35' CMT
FROM 5150- 5115.

4 SHOT / 1 FT SIZED W/ 75 CY CMT (5190')

CHERRY CANYON PERKS S215'-35' (135P) (SCH DLL-3-177)
4 SHOT/1 FT SIZED W/75 SX CMT P5275)

- 100' CMT Plug From 5835' - 5735' (±)

— 100' CMT PLUG FROM 8335'-8235'

— 100' CMT PLUG FROM 10,935' - 10,835'

- 7" CIBP @ 13,495' CAPPED W/ 35' CNT
FROM 13,495' - 13,460'

— 13,520' BAKER MODEL D PKR

— MORROW PERFS 13,621-627; 13687-702

— 13,707

- Morrow PERF 13,838-846 SQZED w/30 str CMT

— 14,314' TOP OF 150 SX CMT PLUG
FROM 14,314 TO 14,514

- 15,240' TOP OF 50 SX CMT PLUG
FROM 15,240-15,440