

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on reverse side)Form approved:
Budget Bureau No. 12 R1421

CLASSIFICATION AND SERIAL NO.

NM1128

CONTAINING, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Dry Hole		7. LAND ACQUISITION NAME	
2. NAME OF OPERATOR C & K PETROLEUM, INC.		8. FARM OR LEASE NAME Morrison Federal	
3. ADDRESS OF OPERATOR 607 Midland National Bank Bldg., Midland, Texas 79701		9. WELL NO. 1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FN and 1980' FE Lines, Sec. 26, T-26-S, R-23-E, Eddy County, New Mexico.		10. FIELD AND POOL OR WHICAT	
14. PERMIT NO.		11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA Sec. 26, T-26-S, R-23-E	
15. ELEVATIONS (Show whether DT, RT, CR, etc.) 4110 Gr.		12. COUNTY (or Parish) 13. STATE Eddy N. M.	

16 Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	☐	PULL OR ALTER CASING	☐
FRACTURE TREAT	☐	MULTIPLE COMPLETION	☐
SHOOT OR ACIDIZE	☐	ABANDON* P & A	☒
REPAIR WELL	☐	CHANGE PLANS	☐
(Other)			

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	☐	REPAIRING WELL	☐
FRACTURE TREATMENT	☐	ALTERING CASING	☐
SHOOTING OR ACIDIZING	☐	ABANDONMENT*	☐
(Other)			

(NOTE: Report results of multiple completion on Well Completion or Re-completion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Notice to Plug and Abandon as follows:

Lower Morrow	40 sx. Cement Plug	8800'-8700'
Strawn	40 sx. Cement Plug	7800'-7700'
Bone Springs	40 sx. Cement Plug	6250'-6150'
	40 sx. Cement Plug	4800'-4700'
	40 sx. Cement Plug	3300'-3200'
Surface Pipe	40 sx. Cement Plug	1930'-1830'
Surface	15 sx. Cement Plug	

Note: The above Plugging Procedure Approved Verbally by Mr. Jim Knauf 2-25-74.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Administrative Supervisor

DATE 2-25-74

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
FEB 27 1974
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO