

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Dry Hole		5. LEASE DESIGNATION AND SERIAL NO. NM 0512668	
2. NAME OF OPERATOR Cities Service Oil Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR Box 4906 - Midland, Texas 79701		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FSL & 1980' FWL of Sec. 21-T25S-R24E, Eddy Co., N.Mex.		8. FARM OR LEASE NAME South Caverns Unit A	
14. PERMIT NO.		9. WELL NO. 1	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3795' GR.		10. FIELD AND POOL, OR WILDCAT Undes. Washington Ranch Morrow	
		11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA Sec. 21-T25S-R24E	
		12. COUNTY OR PARISH Eddy	
		13. STATE New Mexico	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data:

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

T.D. 7550' Shale. Plugged & abandoned. This well was drilled to a T.D. of 7550' and plugged & abandoned in the following manner:

- Set a 35 sx cement plug @ 7050'-6950' across top of Morrow @ 7006'.
- Set a 35 sx cement plug @ 6200'-6100' across top of Strawn @ 6152'.
- Set a 35 sx cement plug @ 5600'-5500' across top of Dean @ 5525'.
- Set a 60 sx cement plug @ 4300'-4200'.
- Set a 60 sx cement plug @ 3100'-3000'.
- Set a 60 sx cement plug @ 1900'-1800'.
- Set a 60 sx cement plug @ 1000'-900' (1/2 in and 1/2 out of 13-3/8" csg set & cemented @ 940').
- Set a 20 sx cement surface plug @ 30'-0' with a 4" Dry Hole Marker extending 4" above the ground to designate a plugged and abandoned location.
- This location will be cleared of all equipment and debris and your office will be notified for final inspection.

RECEIVED

MAR 28 1974

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

E. J. Smith

TITLE

Region Oper. Mgr.

DATE

March 27, 1974

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

DATE