

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF GEOLOGICAL SURVEY

SUNDAY HOTELS AND RESORTS **WEEKLY**
 So this year, for prices as low as \$10 a night, you can enjoy the best of the season. **SEE LIST PAGE 10**

Sec. 33: T-25-S, R-24-E

12. COUNTY OR PARISH	13. STATE
Baldwin	New Mexico

SUBSEQUENT REPORT OF :

WATER SHUT-OFF	REPAIRING WELL
PRODUCER TREATMENT	ALTERING CASING
REPAIRING OF CEMENT	ABANDONMENT*
*When a well is abandoned, it shall be plugged with cement to prevent completion on Well	

The address well was drilled on January 11, 1954 and an 8 1/2 inch (12) inch hole was drilled to 110 feet. On February 12, 1954, 2 1/2 inch casing was run to 100 feet and cemented with 225 sacks Class "C" Ray Cement. Cement was displaced to surface. After W.O.C. 36 hours, the 2 1/2 inch casing was pressure tested at 100 p.s.i. and held ok.

RECEIVED
FEB 18 1974
U. S. GEOLOGICAL SURVEY
ARTESIAN WATER DIVISION

APPROVED BY _____ TITLE _____ DATE _____
 COMMISSION ON ELECTRICITY _____

FEB 20 1954
Buckner

¹⁰ See In re *Chen*, 2005 WL 10000, at *10 (S.D. Cal. Jan. 11, 2005).