

COPIES RECEIVED	
CONTRIBUTION	
DATE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
L - 4868

SUNDRY NOTICES AND REPORTS ON WELLS DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER-	7. Unit Agreement Name
2. Name of Operator	Target Unit
3. Address of Operator	8. Farm or Lease Name
1500 Wilco Bldg. - Midland, Texas 79701	Target Unit
4. Location of Well	9. Well No.
UNIT LETTER J, 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 2 TOWNSHIP 26-S RANGE 25-E NMPM.	1
10. Field and Pool, or Wildcat	
	Wildcat
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
GR. 3587.2	Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐
PULL OR ALTER CASING ☐	OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐	ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOBS ☐	OTHER ☒ DST

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work, SEE RULE 1103.

3-29-74 TD 12,150. Set cmt plugs - 45 sx @ 11,420'; 45 sx (H-Neet) @ 10,797; 100 sx @ 10,296 (w/10# sd/sk & .5 of 1% CFR₂) WOC.

4-1-74 DST #5 9786'-10,100'. 10 min pre flo, good blo 1 min. GTS in 6 min, 100# on ½" ck, 750 Mcf; 10 min, 130# 950 Mcf; SI 1½ hrs, open 3 hrs. 10 min, 145# 1100 Mcf; 30 min, 200#, 1400 Mcf; 45 min, 200#, 1400 Mcf; 180 min, 162#, 1180 Mcf. SI 6 hrs, op 3 hrs. 10 min, 155#, 1150 Mcf; 30 min, 200#, 1400 Mcf; 180 min, 160#, 1170 Mcf. SI 8 hrs, rec 280' drlg fluid; spl cham 240#, 1.1 CFG, no fluid. IHP 5247. PFP - 439 - 506#; ISIP 5314#; FP 426-533#; SIP 5179#; FFP 439-533#; FSIP 5045#; FHP 5112#; Temp 175°.

4-3-74 Prep to P & A by setting following plugs:
45 sx @ 9650'
45 sx @ 7900'
45 sx @ 6325'
50 sx @ 2700'
10 sx @ surface

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Bonnie Husband TITLE Production Clerk DATE 4-3-74

APPROVED BY [Signature] TITLE OIL AND GAS INSPECTOR DATE APR 3 1974

CONDITIONS OF APPROVAL, IF ANY:

BH/1b