

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION
DD APPROVED
a. NM Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

CONFIDENTIAL

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
Pogo Producing Company

3. Address and Telephone No.
P. O. Box 10340, Midland, TX 79702-7340 (915)682-6822

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
1977' FNL & 1938' FWL, Section 1, T24S, R31E

5. Lease Designation and Serial No.
NM-69369

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.
Sundance 1 Federal No. 1

9. API Well No.
30-015-23977 21291

10. Field and Pool, or Exploratory Area

Undes Delaware

11. County or Parish, State

Eddy County, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Intermediate Casing

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU Nabors #301 2/4/95. Drill out cement plugs to 600'. Drilled 11" hole 600' to 4375'. TD reached @ 0630 hrs CST 02/08/95. Ran 102 jts 8-5/8", 24# & 32#, J-55, ST&C casing. Float shoe @ 4375'. Float collar @ 4328'. Howco cemented w/ 1600 sx Halliburton Lite @ 12.7 ppg followed by 200 sx Premium Plus @ 14.8 ppg. Plug down @ 1900 hrs CST 02/08/95. Recovered 350 sx excess cement. ND BOP's and make cut-off. Weld on wellhead and test to 1500 psi. NU BOP's and test to 1500 psi.

APR 28 1995
OIL CON. DIV.
DIST. 2

ACCEPTED FOR RECORD
J. Lora
APR 26 1995
CARLSBAD, NEW MEXICO

14. I hereby certify that the foregoing is true and correct

Signed [Signature]

Title Senior Operations Engineer

Date 3/29/95

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date _____