

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

RECEIVED

JUN 6 1975

3. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.
LG-1175

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT REVENUE CLASSIFICATION. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

O. G. C.
ARTEZIA, OFFICE

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole	7. Unit Agreement Name
2. Name of Operator Jake L. Hamon ✓	8. Farm or Lease Name State LG-1175
3. Address of Operator 611 The Petroleum Building, Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER G 1980 FEET FROM THE North LINE AND 1980 FEET FROM THE East LINE, SECTION 16 TOWNSHIP 26-S RANGE 28-E NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3040.8 K.B.	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to set cast iron bridge plug in 9-5/8" casing @ 6900' & dump 3 sx. cement on BP. Shoot off 9-5/8" casing at approximately 6400'. Pull 9-5/8" casing. Set cement plugs as follows:

- 50 sx plug 4800 - 4900' T/Brushy Canyon
- 50 sx plug 3400 - 3500' T/Cherry Canyon
- 50 sx plug 2400 - 2500' in & out of base of 13-3/8" casing.
- 10 sx plug in top of 13-3/8" casing, with dry hole marker.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Prod. Supt. DATE June 4, 1975

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE JUN 6 1975

CONDITIONS OF APPROVAL, IF ANY:
Intervals between plugs filled w/ mud