No. OF COPIES RECEIVED	3			•	Form C-103
DISTRIBUTION			R	ECEIVED	Supersedes Old C-102 and C-103
ANTAFE	11		NEW MEXICO OIL CONSE	ERVATION COMMISSION	C-102 and C-103 Effective 1-1-65
ile.	11	V		APP 1 0 1075	En Indiana Tura
.S.G.S. AND OFFICE	+	+		APR 1 0 1975	State Fee XX
PERATOR	+-			0 -	5. State Oil & Gas Lease No.
	-1-/-	11		O. C. C.	
	SL	INDRY I	NOTICES AND REPORTS ON		
(DO NOT USE THIS FO	ORM F	OR PROPOS	ALS TO DRILL OR TO DEEPEN OR PLUG BA FOR PERMIT — " (FORM C-101) FOR SUCH	CH TO 1 DIFFERENT BEARANAIA	
on GAS		7	_		7. Unit Agreement Name
WELL WELL Name of Operator		<u> </u>	OTHER- Dry		
ulf Oil Corpora	atic	.		•	8. Form or Lease Hane
Address of Operator	1010			ı ı	Pecos Irrigation State Com
ox 670, Hobbs,	New	Mexic	o 88240		j 1
_ocation of Well					10. Field and Pool, or Wildcat
UNIT LETTER J 1980 FEET FROM THE SOUTH LINE AND 1980 FEET FRO					Wildcat
					THILITIAN TO THE TOTAL OF THE T
THE East LINE, SECTION 20 TOWNSHIP 25-S RANGE 28-E					MPM. (IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII
	777	,,,,,,			
	III		15. Elevation (Show whether D		12. County
	777.	777777		3008' GL	Eddy ()
			propriate Box To Indicate Na	sture of Notice, Report or	Other Data
NOTI	CEC	PEINIE	ENTION TO:	SUBSEQU	JENT REPORT OF:
REFORM REMEDIAL WORK	٦		PLUG AND ABANDON	REMEDIAL WORK	1
MPORARILY ABANDON	Ť		1400	COMMENCE DRILLING OPNS.	ALTERING CASING PLUG AND ABANDONMENT
LL OR ALTER CASING	Ī		CHANGE PLANS	CASING TEST AND CEMENT JOB	TEGG AND ABANDONNENT A
				OTHER	
OTHER				Diversi and should	
Describe Proposed or Co	mplet	ed Operat	ions (Clearly state all pertinent detai	Plugged and abandon	ned. uding estimated date of starting any proposed
work) SEE RULE 1103.				,	g
975. No indica 3,400' to 13,30 rom 12,600' to rom 11,000' to et EZ drill BP paded hole with lass C plug No. 2450', across o. 10 from 2000 ple marker. Wi	12, 10, at ab 8: 13	ns of 80 sa 400', 900', 5500' andonm from 5 -3/8" o 1950 advise	commercial production. ck cement plug No. 2 f 40 sack cement plug No. 6 fro and capped BP with 20 ent mud. Cut and reco 018' to 4918', across shoe at 2415'. Set EZ' and 40 sack cement p	Spotted 36 sack C1 rom 12,980' to 12,78 . 4 from 11,750' to m 9325' to 9225', ac sack Class C cement vered 9-5/8" casing 9-5/8" stub at 4967' drill BP at 2000' a lug No. 11 from 50'	400' at 4:30 PM, March 29, lass H cement plug No. 1 from 30', 80 sack cement plug No. 11,650', 40 sack plug No. 5 cross 9-5/8" shoe at 9260'. plug No. 7 from 5500' to 54 from 4967'. Spotted 75 sack, 50 sack plug No. 9 from 2 and capped with 30 sack plug to surface. Installed dry on. Completed plugging and
bandon on April			20"-30' 13%"-2415-cm 9%" from 4967 to 9.		
Cag. 44	<u> </u>	_ ,	1338-2415-un	4.1.0	4
			9 78" from 4967 to 9	40U	
			. / 1		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
		-31			1,7
			ve is true and complete to the best of	my knowledge and belief.	
ED C.K.	4.	<i>/.</i>		ook Dokmoloum Bordus	A41 10 1075
ED		1 (ritte Proje	ect Petroleum Engine	er DATE April 10,1975
,	/				1641
	- 1	w.		D CAS INSPECTOR	JAN 7 1976

NOITIONS OF APPROVAL, IF ANY