

| | |
|-----------------|-----|
| COPIES RECEIVED | 3 |
| TRIBUTION | |
| FE | 1 |
| FILE | 1 ✓ |
| U.S.G.S. | |
| LAND OFFICE | |
| OPERATOR | 1 |

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

APR 28 1976

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

| | | |
|--|--|---|
| <p align="center">SUNDRY NOTICES AND REPORTS ON WELLS</p> <p align="center"><small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSAL.)</small></p> | | <p>U. C. C. ARTESIA, OFFICE</p> |
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> | 7. Unit Agreement Name | |
| 2. Name of Operator C. E. LeRue and B. N. Mmcy, Jr. ✓ | 8. Farm or Lease Name Pecos Irrigation | |
| 3. Address of Operator P. O. Box 196 Artesia, New Mexico 88210 | 9. Well No. 1 | |
| 4. Location of Well UNIT LETTER J 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 20 TOWNSHIP 25S RANGE 28E NMPM. | 10. Field and Pool, or Wildcat Wildcat | |
| 15. Elevation (Show whether DF, RT, GR, etc.) | | 12. County Eddy |

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

| NOTICE OF INTENTION TO: | | SUBSEQUENT REPORT OF: | |
|--|---|--|---|
| PERFORM REMEDIAL WORK <input type="checkbox"/> | PLUG AND ABANDON <input type="checkbox"/> | REMEDIAL WORK <input type="checkbox"/> | ALTERING CASING <input type="checkbox"/> |
| TEMPORARILY ABANDON <input type="checkbox"/> | CHANGE PLANS <input type="checkbox"/> | COMMENCE DRILLING OPNS. <input type="checkbox"/> | PLUG AND ABANDONMENT <input type="checkbox"/> |
| PULL OR ALTER CASING <input type="checkbox"/> | OTHER <input type="checkbox"/> | CASING TEST AND CEMENT JOBS <input type="checkbox"/> | OTHER Re-entry <input checked="" type="checkbox"/> |

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.



Drilled plugs and cleaned out to a depth of 6300', starting February 26, 1976.

Ran 4976' of 7" casing from inside 9 5/8" to surface. Cemented with 2400 sacks.

Cement Top at 2700'. Perforated from 3357-3369; treated with 1,500 gallons acid.

Perforated from 4446-4461. Treated with packer set at 4430' with 15,000 gallons and 15,000# sand. Testing from Lower Zone.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

| | | |
|---|--------------------------------------|-------------------------|
| SIGNED  | TITLE Operator | DATE 4/26/76 |
| APPROVED BY  | TITLE SUPERVISOR, DISTRICT II | DATE APR 29 1976 |
| CONDITIONS OF APPROVAL, IF ANY: | | |