

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Robert N. Enfield

3. Address and Telephone No.

P. O. Box 2431, Santa Fe, New Mexico 87501 (505) 988-2863

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 660' FWL of Section 20, T-25-S, R-27-E

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

NM 0476505

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

SRM1137

8. Well Name and No.

Cottonwood Draw No. 1

9. API Well No.

30-015-21530

10. Field and Pool, or Exploratory Area

Wildcat - Strawn

11. County or Parish, State

Eddy, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugging operations began November 10, 1994. Attempted to run and set a CIBP at 10,498'. Unable to set CIBP and pull out of the hole. Pushed BP down hole to 10,522'.

Set CIBP at 10,500' K.B. - Spotted 35 sacks cement from 10,500' to 10,365'. Cut and pulled approximately 139 (5763') joints 7" casing.

Cemented across 9 5/8" shoe at 5710' K.B. and 7" stub at 5509' K.B. Cemented from 5763' to 5355' KB with 150 sacks cement.

Tagged cement at 5349' KB.

Cemented from 5763' to 5355' K.B. with 150 sacks cement

Cemented from 5763' to 5349'

Cut 9 5/8" casing at 986' K.B.

Spotted 150 sacks cement from 1036' to 867'

Trip in hole to TOC at 900', spot 100 sack plug from 900' to 805'.

Spot 125 sack plug from 500' to 500'.

Circulate cement to surface with 50 sacks cement.

Weld plate on 13-3/8" casing and install dry hole marker.
cellar has been filled and working pit cleaned out.

All cement used was Class "H" (15.6 ppg and 1.18 yield)

WELL PLUGGED AND ABANONED AS OF NOVEMBER 23, 1994.

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed Sheryl A. Jones

Title Agent for Robert N. Enfield

Date 12/21/94

(This space for Federal or State Review)

(ORIG. SGD.) JOE G. LARA

Approved by
Conditions of approval, if any:

Title PETROLEUM ENGINEER

Date 1/18/95