

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

FOR USE IN APPLICATING FOR
PERMITS (Instructions on
reverse side)

Form 9-331
Budget Pattern No. 42 R1424
5. LEASE DESIGNATION AND SERIAL NO.
NM 20949
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

JUL 21 1975

O. C. C.
ARTESIA, OFFICE

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐	7. UNIT AGREEMENT NAME Hay Hollow Unit
2. NAME OF OPERATOR Great Western Drilling Company ✓	8. FARM OR LEASE NAME
3. ADDRESS OF OPERATOR P. O. Box 1659, Midland, Texas 79701	9. WELL NO. 2
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface Unit Letter F, 1980' FNL & 1980' FWL, Sec. 12, T-26-S, R-27-E	10. FIELD AND POOL, OR WILDCAT Wildcat
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SECT. OR ARBY Sec. 12, T-26-S, R-27-E Unit Letter F
15. ELEVATIONS (Show whether OF, RT, GR, etc.) 3176.1 GR	12. COUNTY OR PARISH Eddy
	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

VENT WATER SHUT-OFF	PULL OR ALTER CASING
FRACURE TREAT	MULTIPLE COMPLETION
SHOOT OR ACIDIZE	ABANDON*
REPAIR WELL	CHANGE PLANS
(Other)	

WATER SHUT-OFF ☒	REPAIRING WELL
FRACURE TREATMENT	ALTERING CASING
SHOOTING OR ACIDIZING	ABANDONMENT*
(Other)	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

7-4-75 Ran 224 Jts. 7-5/8" as follows: 63 Jts. 29.7#/ft., P-110 LT&C, 86 Jts. 33.7#/ft N-80 Buttress, 37 Jts. 26.4#/ft., N-80 LT&C, 38 Jts. 33.7#/ft. P-110 LT&C. Set 9,420' 7-5/8" csg. @ 9401.15' GL Measurement. Cemented as follows: Pumped 500 Gals. mvd flush, followed by 760 sxs. Class "H" with 7.8% salt/sk. plus .2% BJ-R5, plus .2% D 31. Pumped plug with 2100 psi - held. Plug down @ 4:40 A.M., 7-5-75.

7-5-75 Temperature Survey- Top of cement outside 7-5/8" Csg. @ 5900'- inside @ 9360'.

7-6-75 WOC 24 hrs.
Tested 7-5/8" OD, Csg & BOPs to 1,000 psi for 30 minutes- held.

RECEIVED
JUL 18 1975
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE General Superintendent

DATE 7-11-75

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side