

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSTANDARD FORM NO. 100
(Other instructions on reverse side)LICATE
S. OR TOForm approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

N.M. 053862

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Coquina Oil Corporation	8. FARM OR LEASE NAME Black River Fed.
3. ADDRESS OF OPERATOR P. O. Drawer 2960, Midland, Texas 79701	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below. At surface 1980 FWL and 2080 FNL, Sec. 28	10. FIELD AND POOL, OR WILDCAT Wildcat
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 28 T 26S R 25E
15. ELEVATIONS (Show whether DF, RT, CR, etc.) 3704 GL	12. COUNTY OR PARISH Eddy
	13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	FILL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) Drilling Progress ☒	

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Spudded at 1:00 p.m. August 10, 1975. Drilled a 17" hole to 426'. September 12 ran 426.06' of 13 3/8" 48# H-40 STC casing, cemented with 400 sx class C with 2% CaCl₂ 1/4# Flocele. Circ. 100 sx to pit. Displaced w/67 bbls. FW. September 13 tested blind rams to 500 psi for 15", drlg. 11" hole to 1010'. September 24, ran 8 5/8" 32# 8rd J-55 STC casing, Landed at 4752.43', cemented with 300 sx Lite Wate 5# Gilsonite/sx. plus 200 class C 2% CaCl₂, 1/4# Flocele. September 26, drilling ahead with 7 7/8" hole at 5515'.

RECEIVED
OCT - 2 1975
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Engineer

DATE

9-30-75

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
OCT 2 1975
H. L. BECKWITH
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side