

N. M. O. C. C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
SUBMIT IN THE MANNER
(Other Institute or to
verse side)Form approved
Budget Bureau No. 42-R1424
5. LEASE DESIGNATION AND SERIAL NO.

NM-0538562

6. IF INDIAN, ALIQUOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or pump back to a different reservoir.
(APPLICATION FOR PERMIT TO DRILL FOR SUCH PROPOSALS)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR	8. FARM OR LEASE NAME
Coquina Oil Corporation	Black River Federal
3. ADDRESS OF OPERATOR	9. WELL NO.
P. O. Drawer 2560, Midland, TX 79701	1
4. LOCATION OF WELL (Show location clearly and in accordance with any State or Federal Survey or Area)	10. FIELD AND POOL, OR WILDCAT
At surface 1980' FNL & 2080' FNL, Sec 28	Wildcat
11. PERMIT NO.	11. SURVEY, T., R., M., OR BLK. AND SURVEY OR AREA
3704 GR	Sec 28, T26S, R25E
12. ELEVATIONS (Show whether DE, RT, GR, etc.)	12. COUNTY OR PARISH
	Eddy
	13. STATE
	NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NATURE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PUMP OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETION

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE CLASS

(Other)

Drilling Progress

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.*

Spudded @ 1:00 PM, 9-10-75. Drilled 17" hole to 425'. 9-12-75, ran 426.06' of 13 3/8" 48# H-40 STC casing, cemented w/400 sx Class C w/2% CaCl₂, 1/4# flocele. Circ 100 sx to pit. Displaced w/67 bbls FW. 9-13-75, tested blind rams to 500 psi for 15", drlg 11" hole to 1010'. 9-24-75, ran 8 5/8" 32# 8rd J-55 STC casing, landed csg @ 4752.43' & cemented w/300 sx Lite Wate, 5# Gilsonite/sx. Plus 200 Class C 2% CaCl₂, 1/4# Flocele. 10-2-75, 7 7/8" hole caved in @ 9485', worked out pipe, 2 hrs circ & free pipe & re-drill to 9485'. Cont. drilling ahead. 11-13-75, drilling ahead w/7 7/8" hole @ 11,784', drlg slow with no problem.

RECEIVED
NOV 18 1975
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

C. Alan Bump

TITLE

Engineer Asst.

DATE

11-14-75

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side