

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved,
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Active drilling well.		5. LEASE DESIGNATION AND SERIAL NO. 061616	
2. NAME OF OPERATOR Perry R. Bass		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR Box 2760, Midland, Texas 79701		7. UNIT AGREEMENT NAME Poker Lake Unit	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2030' FNL & 2180' FEL of section. Unit letter G.		8. FARM OR LEASE NAME Poker Lake Unit	
14. PERMIT NO.		9. WELL NO. 44	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3303' GL		10. FIELD AND POOL, OR WILDCAT Wildcat	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 10, 25S, 30E.	
		12. COUNTY OR PARISH Eddy	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) Spud date & 8 5/8" csg setting XX	
(Other) ☐		(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 12 1/4" hole @ 3:45 PM, 12-8-75, drilled to 574'.

Ran 12 jts 8 5/8" OD, 24#, K-55 casing. Set @ 568.24' with HOWCO float and guide shoes. Cemented with 375 sks Class C, with 4% gel, 2% CaCl and 1/4# Flocele/sk. Slurry weight 13.5 PPG. Plug down @ 9:00 AM 12-9-75. Circulated out 85 sks. HOWCO bow type centralizers on bottom three (3) joints. WOC 24 hours. Tested casing to 1000# for 30 min. - held OK. Drilled cement and shoe and tested to 50# for 30 min. - held OK. Commenced drilling 7 7/8" hole.

RECEIVED

DEC 17 1975

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

RECEIVED

DEC 17 1975

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED <u>[Signature]</u>	TITLE Senior Petroleum Engineer	DATE December 15, 1975
---------------------------	---------------------------------	------------------------

(This space for Federal or State office use)

APPROVED BY <u>[Signature]</u>	TITLE <u>[Blank]</u>	DATE <u>[Blank]</u>
--------------------------------	----------------------	---------------------

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

687-881