

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
NEW MEXICO COND. COMMISSION
SUBMIT IN TRIP
(Other instructive text aside)
Artesia, NM 88210

Budget Bureau No. 1004-0135
Expires August 31, 1985

ckf

OCT 30 SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. <u>ARTESIA, GAS WELL</u> ☒ OTHER	5. LEASE DESIGNATION AND SERIAL NO. <u>11042</u>
2. NAME OF OPERATOR <u>Bill J. Graham Oil and Gas</u>	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR <u>P. O. Box 7037, Midland, Texas 79708</u>	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) <u>At surface</u> <u>Unit Letter K, 1980 feet from the South line and 1980 feet from the West line, Section 27, Township 26S range 30E NMPM.</u>	8. FARM OR LEASE NAME <u>Ross Draw</u>
	9. WELL NO. <u>5</u>
	10. FIELD AND POOL, OR WILDCAT <u>Ross Draw-Bone Springs</u>
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <u>Sec. 27, T. 26S, R. 30E</u>
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) <u>2996' GR 3013' KB</u>
	12. COUNTY OR PARISH <u>Eddy</u> 13. STATE <u>New Mexico</u>

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☒	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Original Spud: 8-22-76 TD @ 16,326' KB on 12-27-76
Respud: 12-16-77 Sidetrack original hole @ 5759' KB on 12-23-77 TD @ 9052' KB
Current casing:
Surface: 13 3/8 csg set @ 3318' KB, cmt'd to surface.
Production: 7 5/8 csg set @ 8235' KB. Cmt'd in 2 stages 1st w/400 sx then w/700 sx Through Dytool @ 6802'. TOC 5400' by Temp Surv.
Proposed Plugs: (to be set on partner approval to plug, 12-85)

8200'	Top Perfs	CIBP w/35' cmt	7 sx	} Squeeze through perfs if csg cannot be pulled
7300'	Bone Springs	150' cmt	30 sx	
5500'	Brushy Canyon	150' cmt	100 sx	
4310'	Cherry Canyon	100' cmt	70 sx	
3270 - 3370'	Delaware Lime	100' cmt	70 sx	
1575'	Top Salt	100' cmt	70 sx	
350'	Fresh Water	100' cmt	70 sx	

50' to surface

I hereby certify that the foregoing is true and correct
SIGNED Rodney L. Seale *Rodney Seale* TITLE Engineer DATE August 20, 1985
(This space for Federal or State office use)
APPROVED BY Mark Rodda *Mark Rodda* TITLE _____ DATE 10-29-85
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side