

NMOCC COPY

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN THE
REVERSE SIDE

Copy to SF

5. LEASE DESIGNATION AND SERIAL NO.
NM 05-0850
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

NA

7. UNIT AGREEMENT NAME

NA

8. FARM OR LEASE NAME

Hudson Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat
11. SEC. T., R., M., OR BLM. AND
SURVEY OR AREA

17-26S.-25E.

12. COUNTY OR PARISH 13. STATE

EDDY

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

MAY 4 1977

O.C.C.
ARTESIA, OFFICE

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Leland A. Hodges, Trustee

3. ADDRESS OF OPERATOR

P. O. Box 3400, Albuquerque, NM 87110

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980' FSL & 990' FEL of Section 17, 26S., 25E.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3741 GR 3745 DF

12. COUNTY OR PARISH 13. STATE

EDDY

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEXT WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETION

FRACTURE TREATMENT

ALTERING CASING

ABANDON OR ACIDIZE

ABANDON*

ABANDONING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

We propose to plug and abandon this well at the current total depth of 1317' by (1) setting 100' cement plugs across the top of the Delaware lime (1192') and the bottom of the surface casing (103'), (2) filling the hole between plugs with U.S.G.S. specified drilling mud, (3) setting a cement plug and required marker in the top of the ~~SMF~~ surface casing, and (4) filling the pits and leveling and restoring the location and new road in accordance with BIM specifications.

RECEIVED

MAY 03 1977

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED *Leland A. Hodges*

TITLE Geologist

DATE 4-12-77

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side