

Form 7-6371
May 1963UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYINSTRUCTIONS
(Reverse side)Form approved
by the Department of the Interior
3. LEASE DESIGNATION AND SERIAL NO.
NA
4. IF INDIAN, AGENCY AND TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to design or install a well to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☒ OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR **Leland A. Hodges, Trustee**

3. ADDRESS OF OPERATOR **P. O. Box 3400, Albuquerque, NM 87110**

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface
1980' FSL & 990' FEL of Section 17, 26S., 25E.

14. PERMIT NO. **30-215-20083**

15. ELEVATIONS (Show whether DE, RL, OR, etc.)
3741 GR 3745 DE

RECEIVED

FEB 26 1979

O. C. C.
ARTESIA, OFFICE

7. UNIT AGREEMENT NAME
NA

8. FARM OR LEASE NAME
Hudson Federal

9. WELL NO.
1

10. FIELD AND POOL OR WELL AT
Wildcat

11. SEC., T., R., M., OR BBL. AND SURVEY OR AREA
17 26S., 25E.

12. COUNTY OR PARISH, 13. STATE
Eddy NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐ PULL OR ALTER CASING ☐

FRACTURE TREAT ☐ MULTIPLE COMPLETE ☐

SHOOT OR ACIDIZE ☐ ABANDON* ☐

REPAIR WELL ☐ CHANGE PLANS ☐

(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐ REPAIRING WELL ☐

FRACTURE TREATMENT ☐ ALTERING CASING ☐

SHOOTING OR ACIDIZING ☐ ABANDONMENT* ☒

(Other) ☐ **surface casing and plugging** ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

3-29-77 spudded well

3-31-77 TD 103' Ran 103' 8 5/8" 28#
used casing, cemented w/50 sax class C w/4% calcium chlorid, circulated to surface, WOC 18 hrs. Tested casing to 600#. Held ok.

4-10-77 TD 1317 Ran BHC sonic log. Flushed hole w/nitrogen.

4-12-77 Ran wire line - top of fluid 200'. Circulated out 200' sulfur water. Mixed mud to U.S.G.S. specs. Set 16 sack cement plug from 1150 to 1250, set 22 sack plug from 40' to 140', and set 12 sack cement plug in top of surface casing. Abandoned location for subsequent leveling and restoration after pits have dried.

RECEIVED

MAY 02 1977

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED **Bert Dargatz**TITLE **Geologist**DATE **4-15-77**

(This space for Federal or State office use)

APPROVED BY **Joe S. Lara**TITLE **ACTING DISTRICT ENGINEER**DATE **FEB 23 1979**

CONDITIONS OF APPROVAL, IF ANY: