

INMOC COPY

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPI
(Other instructions
reverse side)FE•
TO•Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 19423

6. INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

White City Fed "10" Com

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

White City (Penn)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 10, T25S, R26E

12. COUNTY OR PARISH

Eddy

13. STATE
New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. ☐ OIL
WELL ☐ GAS
WELL ☒ OTHER

2. NAME OF OPERATOR

Mesa Petroleum Co ✓

3. ADDRESS OF OPERATOR

1000 Vaughn Building/Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State regulations.
See also space 17 below.)
At surface

1650' FNL & 1650' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DE, RE, OR, etc.)

3412 GR

C. C. C.
ANTHONY, OFFICE

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PILE OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) 10-3/4" Casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent
to this work.) *

Drilled 14-3/4" hole to 1780' on 4-9-78. Ran 42 jts 10-3/4" 40.5# ST&C casing (1784' overall) with insert float 1 jt up. Installed centralizer on top of jt #1, 3, and 5. Set casing shoe at 1780' RKB. Cemented with 1200 sx Class "C" + 2% cc + 1/4# celloflakes + 5# gilsonite followed by 200 sx Class "C" + 2% cc. PD at 2:00 AM 4-10-78. Circ 60 sx to surface. WOC 18 hours. Tested casing to 2000 psi - 30" - ok. Reduced hole to 9 1/2" and drilled ahead.

18. I hereby certify that the foregoing is true and correct

SIGNED

Wicki Harrison

TITLE

Agent

DATE

4-12-78

(This space for Federal or State office use)

APPROVED BY

J. L. J. L. J.

TITLE

ACTING DISTRICT ENGINEER

DATE

APR 14 1978

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

XC: JLF, JWH, MEC, FILE, USGS, HNG