

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
ARTESIA	/
ILL	/
U.S.	
AND OFFICE	
PERATOR	/

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION
APR 21 1978

Form O-101
Supersedes O-11
O-102 and O-103
Effective 1-1-65

O. C. C.
ARTESIA, OFFICE

SUNDY NOTICES AND REPORTS ON WELLS DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR RE-ENTER A WELL OR TO A DEEPER RESERVOIR. USE APPLICATION FOR PERMIT TO DRILL (SEE RULE 1103 FOR PROPOSALS.)		5a. Indicate Type of Lease State ☐ Fee ☒
		5. State Oil & Gas Lease No.
		7. Unit Agreement Name
Name of Operator C. E. LaRue and B. N. Muncy, Jr.		6. Name of Lease Name Hammond
Address of Operator P O Box 196 Artesia, NM 88210		9. Well No. 1
Location of Well UNIT LETTER E 1980 FEET FROM North LINE AND 660 FEET FROM THE West LINE, SECTION 21 TOWNSHIP 25 N RANGE 28 E NMPM.		10. Field and Pool, or Wildcat Wildcat Delaware
15. Elevation (show whether DE, KT, GR, etc.) 2994.2		12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO: REFORM REMEDIAL WORK ☐ IMPROVABLY ABANDON ☐ LL OR ALTER CASING ☐ OTHER ☐		SUBSEQUENT REPORT OF: PLUG AND ABANDON ☐ CHANGE PLANS ☐ OTHER ☐		REMEDIAL WORK ☐ COMMENCE DRILLING OPNS. ☐ CASING TEST AND CEMENT JOBS ☐ OTHER ☐		ALTERING CASING ☐ PLUG AND ABANDONMENT ☐ Surface Pipe ☒	
--	--	---	--	--	--	--	--

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting, any proposed work.) SEE RULE 1103.

Spudded 3/4/78, ran 532' of 8 5/8" casing and circulated cement with 190 sacks Class C cement with 2% Ca Cl, 15 sacks to pit. 3/5/78 Waited on cement 18 hours, pressure tested casing @ 600# for 30 minutes, no leakage, 3/6/78.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

TO: <i>[Signature]</i>	TITLE: Operator	DATE: 4/18/78
APPROVED BY: <i>[Signature]</i>	TITLE: SUPERVISOR, DISTRICT II	DATE: APR 27 1978

EDITIONS OF APPROVAL, IF ANY:

3-31-78

C & L Run called T & A

need C-103 on surface csg.

spot 355X.	3350-3450
" "	2500-2600
" "	2150-2250
" "	1100-1200
" "	500-600

surface plug w/ marker