

NMOCC COPY
UNIT. STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate
(Other Instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 9553

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "J"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat-Morrow

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

6-26-27

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3300.5 GR

O. C. C.

ARTESIA, OFFICE

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

16.

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other) Spud x Set casing

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

On 3-30-78 MGF Drilling Co. (Rig #26) spudded a 20" hole at 2:30 PM. Drilled to TD of 465' and set 16" 65# H-40 ST&C casing at 465'. Cemented with 575 sacks incor. Plug down at 6:30 PM 4-2-78. Circulated 65 sacks. WOC 28 hrs. Tested casing with 1000# for 30 minutes. OK. Reduced hole to 14 3/4" and resumed drilling.

Drilled to TD of 2000' and set 10 3/4" 40.5 K-55 ST&C casing at 2000'. Cemented with 1150 sacks Howco lite and 200 sacks Class C. Plug down at 4:00 PM 4-7-78. Circulated 75 sacks. WOC 18 hrs. Tested casing with 1000# for 30 minutes. OK. Reduced hole to 9 1/2" and resumed drilling.

Drilled to TD of 10,422' and set 7 5/8" 26.4#, 29.7#, and 39# N-80 and S-95 LT&C casing at 10,422'. Cemented with 1450 sacks Trinity lite and 200 sacks Class H. Plug down at 9:30 PM 5-2-78. Ran temperature survey and found top of cement at 2475'. WOC 50 3/4 hrs. Tested casing with 2000# for 30 minutes. OK. Reduced hole to 6 1/2" and resumed drilling.

Drilled to TD of 10,874'. Core #1 10,874'-10,934'. Core #2 10,934'-10,994'. Core #3 10,994'-11,034'. Core #4 11,034'-11,042'. Core #5 11,042'-11,075'. Resumed drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Admin. Analyst

DATE

5-19-78

(This space for Federal or State office use)

APPROVED BY

TITLE

ACTING DISTRICT ENGINEER

DATE

MAY 30 1978

CONDITIONS OF APPROVAL, IF ANY:

0+4-USGS-A

1-Div

1-Susp

1-RC

*See Instructions on Reverse Side