

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR  
Amoco Production Company

3. ADDRESS OF OPERATOR  
P.O. Drawer "A" Levelland, TX 79336

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 2180 FNL & 660 FWL, Sec 6, (Unit E,  
AT TOP PROD. INTERVAL: SW $\frac{1}{4}$ , NW $\frac{1}{4}$ )  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☒  
(other)

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
NM 9553  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Federal "J"  
9. WELL NO.  
1  
10. FIELD OR WILDCAT NAME  
Wildcat - Delaware  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
6-26-27  
12. COUNTY OR PARISH  
Eddy  
13. STATE  
NM  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3300.5 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Evaluated well and determined well was not commercially productive. Propose to plug and abandon well using the following procedure. Cut and pull casing. Spot 30 sx Class C cement plug 4950' - 4800'. Spot 40 sx Class C cement plug in and out of casing stub. Spot 40 sx Class C cement plug 1955' - 2055' across 10 3/4" casing shoe (Note: if the casing is pulled above 2000', this plug will not be used.). Spot 20' Class C cement plug at surface. Erect P X A marker and complete required site clean-up.

RECEIVED  
NOV 9 1978  
U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED Rennis Evans TITLE Assist. Admin Analyst DATE 11-8-78

APPROVED BY Lee J. Lara  
CONDITIONS OF APPROVAL, IF ANY:

0+4-USGS-A 1-Getty 1-Gulf  
1-Houston Box 1231 Box 1150  
1-Susp Midland, TX Midland, TX  
1-DE

\*See Instructions on Reverse Side

NOV 21 1978