

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☒

2. NAME OF OPERATOR
Amoco Production Company

3. ADDRESS OF OPERATOR
P. O. Drawer "A", Levelland, TX 79336

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FNL & 1980' FEL, Sec. 28
AT TOP PROD. INTERVAL: (Unit G, SW/4, NE/4)
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☐
☐
☐
☐
☐
☐
☐
☒

5. LEASE
NM-26103

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
RECEIVED

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Federal "K"

FEB 27 1980

9. WELL NO.
1

O. C. D.
ARTESIA, OFFICE

10. FIELD OR WILDCAT NAME
Und. Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
28-25-27

12. COUNTY OR PARISH
Eddy

13. STATE
New Mexico

14. API NO.

30-015-22713

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3111.8 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged and abandoned well using the following procedure. Spot 60 sacks of Class H plug cement at 11,800'-12,000'. Spot 55 sacks of Class H plug cement at 10,900'-11,100'. Spot 35 sacks Class H plug cement at 8350'-8500', and spot 35 sacks of Class H plug cement at 4850'-5000'. Released rig at 2:30 p.m., 3/11/79.

and pulled

Moved in casing pullers 4/6/79. Cut 5-1/2" casing at 1710'. Spot 40 sacks of Class H plug cement in and out of casing stub. Spot 10 sacks of Class H plug cement at surface. Erect P&A marker. Level and clean up location. Final Report.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Ray Co

TITLE Admin. Supv.

DATE 4/9/79

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

0+4-USGS, A

1-Houston

1-Suspense

1-CC

1-Napco

1-Mesa Petro.

1-EPNG

1-Sabine Prod.

ACTING DISTRICT ENGINEER

TITLE

DATE

FEB 26 1980