

## NMOCC COPY

## United States Department of the Interior CFIVED

GEOLOGICAL SURVEY
P. 0. Drawer U

Artesia, New Mexico 88210

JAN 3 1 1979

U. C. C.
ARTESIA, OFFICE

JAN 2 2 1979

Florida Gas Exploration Co. Vaughn Building, Suite 900 Midland, Texas 79701 FLORIDA GAS EXPLORATION COMPANY
Ross Draw Unit Well No. 7
1980 FSL 1980 FEL Sec. 26, T26S, R30E
Eddy County Lease No. NM-11042

Above Data Required on Well Sign

## Gentlemen:

Your APPLICATION FOR PERMIT TO DRILL the above-described well to a depth of 14,500 feet to test the Morrow is hereby approved subject to compliance with the OIL AND GAS OPERATING REGULATIONS (30 CFR 221) and the following conditions:

- 1. Drilling operations authorized are subject to compliance with the attached General Requirements for Oil and gas Operations on Federal Leases, dated July 1, 1978.
- 2. Prior to commencing construction of road, pad, or other associated developments, operator will provide the dirt contractor with a copy of the Surface Use Plan and these Conditions of Approval including General Requirements.
- 3. Submit a Daily Report of Operations from spud date until the well is completed and the Well Completion Report (form 9-330) is filed. The report should be not less than  $8" \times 5"$  in size and each page should identify the well.
- 4. All permanent above-ground structures and equipment shall be painted in accordance with the attached Painting Guidelines. The color used should simulate sandstone brown (Federal Standard Color No. 595A, color 20318 or 30318).
- 5. Before drilling below the 9-5/8" casing, the blowout preventer assembly will consist of a minimum of one annular type and two ram type preventers.
- 6. A kelly cock will be installed and maintained in operable condition.
- 7. After setting the 9-5/8" casing string and before drilling into the Wolfcamp formation, the blowout preventers and related control equipment shall be pressure tested to rated working pressures by an independent service company. Any equipment failing to test satisfactorily shall be repaired or replaced. This office should be notified in sufficient time for a representative to witness the tests and shall be furnished a copy of the pressure test report.