

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT AN ORIGINAL  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. NAME OF OPERATOR  
FLORIDA EXPLORATION COMPANY

3. ADDRESS OF OPERATOR  
SUITE 900 VAUGHN BUILDING

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface  
1980' FSL & 1980' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)  
3019.5' GL

OCT 22 1982

O. C. D.  
ARTESIA, OFFICE

5. LEASE DESIGNATION AND SERIAL NO.  
30-011042

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME  
ROSS DRAW UNIT

8. FARM OR LEASE NAME  
ROSS DRAW

9. WELL NO.  
07

10. FIELD AND POOL, OR WILDCAT  
WOLFCAMP

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA  
SEC 26 T26S R30E

12. COUNTY OR PARISH  
EDDY

13. STATE  
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

REMEDIAL WORK-PERFORATE  
(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

06-15-82


Perforate 4 spf @ 12,061, 63, 75, 82 & 88'. Acidize with 3000 gal 7½% Dolowash & 70 ball sealers. Average pressure 6700-6750#.

06-18-82

Perforate 1 spf @ 11,850-862 & 11,868-874'.

06-27-82

Acidize with 10,000 gal 15% MS acid. Average pressure 7000#. Swabbed and flowed 2 days. On 6-29-82, set Baker Lok-Set packer at 11,558'. Return to sales line.



18. I hereby certify that the foregoing is true and correct

SIGNED

*Alan Burrow*

TITLE

SR TA ENGINEERING

DATE

JULY 08, 1982

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF

ACCEPTED FOR RECORD

(ORIG. SGD.) DAVID R. GLASS

TITLE

DATE

OCT 21 1982

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

See Instructions on Reverse Side