

9. WELLSITE LAYOUT.

- A. Exhibit D shows the dimensions of the well pad and reserve pits, and the location of major rig components.
- B. The ground surface at the drilling location is sloping down toward the east. Cutting will be required to level the pad area, which will be covered with at least six inches of compacted caliche.
- C. The reserve pits will be plastic lined.
- D. The pad and pit area has been staked and flagged.

10. PLANS FOR RESTORATION OF THE SURFACE.

- A. After finishing drilling and/or completion operations, all equipment and other material not needed for further operations will be removed. The location will be cleared of all trash and junk, to leave the wellsite in as aesthetically pleasing a condition as possible.
- B. Unguarded pits, if any, containing fluids will be fenced until they have been filled.
- C. If the proposed well is non-productive, all rehabilitation and/or vegetation requirements of the Bureau of Land Management and the United States Geological Survey will be complied with and will be accomplished as expeditiously as possible. All pits will be filled and leveled within 90 days after abandonment.

11. TOPOGRAPHY.

- A. The wellsite and access route are located in a hilly area.
- B. The top soil at the wellsite is rocky.
- C. The vegetation cover at the wellsite is moderately sparse, with prairie grasses, some yucca, and miscellaneous weeds.
- D. No wildlife was observed but it is likely that rabbits, lizards, insects, and rodents traverse the area. The area is used for cattle grazing.
- E. There are no ponds, lakes, streams, or rivers within several miles of the wellsite.
- F. The wellsite is located on federal surface.
- G. There is no evidence of any archaeological, historical, or cultural sites in the vicinity of the location.