STATE OF NEW MEXICO "NERGY AND MINERALS DEPARTMENT

MB. OF COPIES ACCCIVES		
DISTRIBUTION		<u> </u>
SANTA FE		
FILE		0
U.\$.0.5.		
LAND OFFICE	Ш.	<u> </u>
OPERATOR	Ti	

CONDITIONS OF APPROVAL, IF ANY:

OIL CONSERVATION DIVISION

P. O. BOX 2088	Revised 19-1-78
SANTA FE, NEW MEXICO 87501	
U.S.G.S.	5a, Indicate Type of Lease
LAND OFFICE	State X Fue
OPERATOR	5, State Oil & Gas Lease No.
	L-4687
SUNDRY NOTICES AND REPORTS ON WELLS (60 NOT USE THIS FORM FOR PROPOSALS TO DRILL OF TO DEEPEN OF PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.) DECEMBED	
OIL X GAS WELL OTHER-	7. Unit Agreement Name
Name of Operator MAR 1 2 1981	8. Farm or Lease Name
Amoco Production Company	State GG Com.
, Address of Operator O. C. D.	9. Well No.
P. O. Box 68 Hobbs, NM 88240 ARTESIA, OFFICE	10 Field and Dool, or Wildest
Location of Well 1 1980 South	10. Field and Pool, or Wilded
UNIT LETTER , 1300 FEET FROM THE SOUGH LINE AND COOL FEET FROM THE	
THE West LINE, SECTION 15 TOWNSHIP 25-S RANGE 28-E NM	PM.
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
2988.3 GL	Eddy (
Check Appropriate Box To Indicate Nature of Notice, Report or	Other Data
• • •	ENT REPORT OF:
NOTICE OF INVENTION TO	
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
FULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JQB	Diug V abandan (V)
OTHER	Plug X abandon X
OTHER	
Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, included	ling estimated date of starting any proposed
work) SEE RULE 1103. 13690	
111/20/0	
Plugged well per the following:	
Set a cast iron bridge plug at 8850' and capped with 35' Class H cen	
Set a cast rion bridge plug at 7500' and capped with 35' Class H cen	ment.
Set a 100' (40 sack) Class H cement plug at 6250'-6350'.	
Set a 100' (40 sack) Class H cement plug at 2480'-2580'.	
Cut casing at 2050' and pull 47 joints 9-5/8" casing. Set a 100' (60 sack) Class H cement plug at 2000'-2100'.	
Set a 100' (82 sack) Class H cement plug at 2000'-2100'.	
Set a 20 sack Class H cement surface plug and installed P X A	marker.
0+4-NMOCD, A 1-Hou 1-Susp 1-W. Stafford, Hou 1-GLF	
is, I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
Genald I take Title Admin. Analyst	DATE 3-10-81
HEARD THE	
ORL AND GAS INSPECTOR	MAR 1 6 1982