

CEMENTING TO PLUG AND ABANDON	PLUG # 1	PLUG # 2	PLUG # 3	PLUG # 4	PLUG # 5	PLUG # 6	PLUG # 7	PLUG # 8
23. Cementing date	7/8/88							
24. Size of hole or pipe plugged (in.)	4-1/2							
25. Depth to bottom of tubing or drill pipe (ft.)	830							
26. Sacks of cement used (each plug)	65							
27. Slurry volume pumped (cu. ft.)	112							
28. Calculated top of plug (ft.)	Surface							
29. Measured top of plug, if tagged (ft.)								
30. Slurry wt. (lbs/gal)	13.5							
31. Type cement	Premium Plus							

CEMENTER'S CERTIFICATE: I declare under penalties prescribed in Sec. 91.143, Texas Natural Resources Code, that I am authorized to make this certification, that the cementing of casing and/or the placing of cement plugs in this well as shown in the report was performed by me or under my supervision, and that the cementing data and facts presented on both sides of this form are true, correct, and complete, to the best of my knowledge. This certification covers cementing data only.

Steve Engleman - Cementer

Name and title of cementer's representative

Box 610

HALLIBURTON SERVICES

Cementing Company

Signature

Steve Engleman

Monahans, Texas 79756

City,

State, Zip Code

915/943-2721

Tel: Area Code Number

Date: 9-15-88 mo. day yr.

OPERATOR'S CERTIFICATE: I declare under penalties prescribed in Sec. 91.143, Texas Natural Resources Code, that I am authorized to make this certification, that I have knowledge of the well data and information presented in this report, and that data and facts presented on both sides of this form are true, correct, and complete, to the best of my knowledge. This certification covers all well data.

R. C. Slack

Typed or printed name of operator's representative

Operator

Title

Signature

R. C. Slack

P. O. Drawer 820

Address

Pecos

City,

TX 79772

State, Zip Code

915/445-3827

Tel: Area Code Number

9-15-88

Date: mo. day yr.

Instructions to Form W-15, Cementing Report

IMPORTANT: Operators and cementing companies must comply with the requirements of the Commission's Statewide Rules 8 (Water Protection), 13 (Casing, Cementing, Drilling, and Completion), and 14 (Well Plugging). For offshore operations, see the requirements of Rule 13 (c).

A. What to file. An operator should file an original and one copy of the completed Form W-15 for each cementing company used on a well. The cementing of different casing strings on a well by one cementing company may be reported on one form. Form W-15 should be filed with the following:

- An initial oil or gas completion report, Form W-2 or G-1, as required by Statewide or special field rules;
- Form W-4, Application for Multiple Completion, if the well is a multiple parallel casing completion; and
- Form W-3, Plugging Record, unless the W-3 is signed by the cementing company representative. When reporting dry holes, operators must complete Form W-15, in addition to Form W-3, to show any casing cemented in the hole.

B. Where to file. The appropriate Commission District Office for the county in which the well is located.

C. Surface casing. An operator must set and cement sufficient surface casing to protect all usable-quality water strata, as defined by the Texas Department of Water Resources, Austin. Before drilling a well in any field or area in which no field rules are in effect or in which surface casing requirements are not specified in the applicable rules, an operator must obtain a letter from the Department of Water Resources stating the protection depth. Surface casing should not be set deeper than 200 feet below the specified depth without prior approval from the Commission.

D. Centralizers. Surface casing must be centralized at the shoe, above and below a stage collar or diverting tool, if run, and through usable-quality water zones. In nondeviated holes, a centralizer must be placed every fourth joint from the cement shoe to the ground surface or to the bottom of the cellar. All centralizers must meet API specifications.

E. Exceptions and alternative casing programs. The District Director may grant an exception to the requirements of Statewide Rule 13. In a written application, an operator must state the reason for the requested exception and outline an alternate program for casing and cementing through the protection depth for strata containing usable-quality water. The District Director may approve, modify, or reject a proposed program. An operator must obtain approval of any exception before beginning casing and cementing operations.

F. Intermediate and production casing. For specific technical requirements, operators should consult Statewide Rule 13 (b) (3) and (4).

G. Plugging and abandoning. Cement plugs must be placed in the wellbore as required by Statewide Rule 14. The District Director may require additional cement plugs. For onshore or inland wells, a 10-foot cement plug must be placed in the top of the well, and the casing must be cut off three feet below the ground surface. All cement plugs, except the top plug, must have sufficient slurry volume to fill 100 feet of hole, plus ten percent for each 1,000 feet of depth from the ground surface to the bottom of the plug.

To plug and abandon a well, operators must use only cementers approved by the Director of Field Operations. Cementing companies, service companies, or operators can qualify as approved cementers by demonstrating that they are able to mix and pump cement in compliance with Commission rules and regulations.

Operator: Fill in shaded areas.
 Driller: Fill in other items.

Form W-15
 Cementing Report
 Rev. 4/1/83
 483-045

RAILROAD COMMISSION OF TEXAS
 Oil and Gas Division

0665365

1. Operator's Name (As shown on Form P-5, Organization Report) R. C. SLACK		2. RRC Operator No.	3. RRC District No.	4. County of Well Site Eddy (New Mexico)
5. Field Name (Wildcat or exactly as shown on RRC records)			6. API No. 42-	7. Drilling Permit No.
8. Lease Name Castile Federal		9. Rule 37 Case No.	10. Oil Lease/Gas ID No.	11. Well No. 1

ASING CEMENTING DATA:		SURFACE CASING	INTER-MEDIATE CASING	PRODUCTION CASING		MULTI-STAGE CEMENTING PROCESS	
				Single String	Multiple Parallel Strings	Tool	Shoe
2. Cementing Date							
3. • Drilled hole size							
• Est. % wash or hole enlargement							
4. Size of casing (In. O.D.)							
5. Top of liner (ft.)							
6. Setting depth (ft.)							
7. Number of centralizers used							
8. Hrs. waiting on cement before drill-out							
19. API cement used: No. of sacks ▶							
	Class ▶						
	Additives ▶						
No. of sacks ▶							
	Class ▶						
	Additives ▶						
No. of sacks ▶							
	Class ▶						
	Additives ▶						
20. Slurry pumped: Volume (cu. ft.) ▶							
	Height (ft.) ▶						
Volume (cu. ft.) ▶							
	Height (ft.) ▶						
Volume (cu. ft.) ▶							
	Height (ft.) ▶						
Volume (cu. ft.) ▶							
	Height (ft.) ▶						
Was cement circulated to ground surface (or bottom of cellar) outside casing?							

Remarks

OVER