

- B. Drilling fluids will be allowed to evaporate in the reserve pit until the pit is dry. The pit will then be back-filled and restored as near as possible to the original surface conditions.
- C. Water produced during operations will be collected in steel tanks until hauled to an approved disposal system; or else a separate disposal application will be submitted to the USGS for appropriate approval.
- D. Oil produced during operations will be stored in steel tanks at the drill site.
- E. All laws and regulations governing human waste disposal will be complied with.
- F. Trash, waste paper, garbage and junk will be buried in a separate trash pit and covered with a minimum of 24" of dirt. All waste material will be contained to prevent scattering by the wind.
- G. All trash and debris will be buried or removed from the well site within 30 days after finishing drilling and/or completion operations.

8. ANCILLARY FACILITIES

- A. None required at this time.

9. WELLSITE LAYOUT

- A. Exhibit D shows the dimensions of the well pad and reserve pits, and the location of major rig components.
- B. The drilling location lies near the top of small hill which drains eastward to the Black River. The pad area will be cleared of mesquite and greasewood before covering with at least 6 inches of compacted caliche. No cutting will be required.
- C. The reserve pits will be plastic lined.
- D. The pad and pit area has been staked and flagged.

10. PLANS FOR RESTORATION OF THE SURFACE

- A. After finishing drilling and/or completion operations all equipment and other material not needed for further operations will be removed. The location will be cleared of all trash and junk, to leave the wellsite in as aesthetically pleasing a condition as possible.