

N.M.O.C.D. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN DUPLICATE
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 030457

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL ☐ GAS ☒ OTHER ☐
WELL WELL

MAY 13 1981

2. NAME OF OPERATOR

PERRY R. BASS

O. C. D.

3. ADDRESS OF OPERATOR

ARTESIA, OFFICE

MAY 7 1981

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)
See also space 17 below.)
At surface

Box 2760, MIDLAND, TX, 79702

OIL & GAS
GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

660' FNL; 1980' FNL OF SECTION - UNIT LETTER B.

7. UNIT AGREEMENT NAME

POKER LAKE UNIT

8. FARM OR LEASE NAME

POKER LAKE UNIT

9. WELL NO.

50

10. FIELD AND POOL, OR WILDCAT

WILDCAT

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

SEC. 4, T. 25S, R. 31E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3436.8' GL

12. COUNTY OR PARISH

13. STATE

EDDY

N. MEX.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) 7" CSG. & 5" LINER

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

DRILLED 8 3/4" HOLE TO 12,651'. PLUG BACK TO 12,632'

RAN 292 JTS. 7" CSG. (22 JTS. 7" 26# N-80 BUTT. LTIC CSG.) (119 JTS. 7" 23# N-80 LTIC CSG.) (90 JTS. 7" 23# S-95 LTIC CSG.) (61 JTS. 7" 26# S-95 LTIC CSG.) SET @ 12,665' CEMENTED W/300 SKS CLASS "H" BUMPED PLUG @ 7: AM CST. SEPTEMBER 30, 1980. WOC 22 HRS. TESTED BOP, TO 5000#, HYDRIL TO 1500# CK. MANIFOLD & KELLY COCK TO 5,000# & CSG SHOE, & CSG. TO 2200# HELD O.K. COMMENCED DRILLING 6 1/4" HOLE.

DRILLED 6 1/4" HOLE TO 15,356'
RAN 73 JTS 5" CSG. (37 JTS. 18# N-80 HYDRIL SFS-P) (36 JTS. 18# P-110 HYDRIL SFS-P CSG.) SET @ 15,345'
CEMENTED W/400 SKS LIGHT. DID NOT BUMP PLUG HAD FULL RETURNS, HOLE STOOD FULL. WOC 11 HRS.
TEST LINER TO 2000# FOR 30 MIN HELD O.K.

18. I hereby certify that the foregoing is true and correct

SIGNED

H. J. Nix, Jr.

TITLE

A. Prod. Clerk

DATE

May 5, 1981

(This space for Federal or State office use)

APPROVED BY:

ROGER A. CHAPMAN

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

MAY 11 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side