

C/SZ

NM OIL CONS. COMMISSION
Drawer DD
Artesia, NM 88210

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other PXA
well well

2. NAME OF OPERATOR
Amoco Production Company

3. ADDRESS OF OPERATOR
P. O. Box 68, Hobbs, New Mexico 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2310' FNL X 430' FWL
AT TOP PROD. INTERVAL: (Unit E, SW/4, NW/4)
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☐
☐
☐
☐
☐
☐
☐
☒

5. LEASE
NM-16814

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Federal "AY"

MAR 10 1983

9. WELL NO.
1

O. C. D.

10. FIELD OR WILDCAT NAME
Brushy Draw Delaware

ARTESIA, OFFICE

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
20-26-30

12. COUNTY OR PARISH
Eddy

13. STATE
NM

14. API NO.
30-015-23307

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3007.6 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in service unit 12-23-82. Pulled tubing. Ran CIBP set at 3370'. Pressure tested to 500 psi for 15 minutes. Tested OK. Pumped 33 sacks class C cement from 3370'-3270'. Displaced hole with 10# gelled brine water. Spotted a 33 sack class C cement plug from 665'-565'. Pumped a 16 sack class C cement plug from 50' to surface. Welded on cap and erected PXA marker.

0+6-BLM, R 1-HOU 1-DMF 1-W. Stafford, HOU

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Mark Freeman

TITLE

Ast. Adm. _____ 83

APPROVED

(This space for Federal or State use)

APPROVED BY

James A. Gillham

TITLE

CONDITIONS OF APPROVAL, IF ANY:

MAR 9 1983

FOR

JAMES A. GILLHAM
DISTRICT SUPERVISOR

JAN 19 1983

OIL & GAS
MINERALS MGMT. SERVICE
ROSWELL, NEW MEXICO

*See Instructions on Reverse